DIN EN 1793-4:2015-05 (E)

Road traffic noise reducing devices - Test method for determining the acoustic performance - Part 4: Intrinsic characteristics - In situ values of sound diffraction

Contents

Page

Foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms, definitions and symbols 7
3.1 Terms and definitions 7
3.2 Symbols 8

4 Sound diffraction index difference measurements 10
4.1 General principle 10
4.2 Dimensions and specifications 10
4.2.1 Added devices 10
4.2.2 Reference walls 10
4.2.3 In situ tests 11
4.3 Positions of the sound source 11
4.4 Position of the microphone(s) 12
4.5 Free-field measurements 13
4.6 Measured quantity 17
4.7 Measuring equipment 18
4.7.1 Components of the measuring system 18
4.7.2 Sound source 19
4.7.3 Test signal 20
4.8 Data processing 20
4.8.1 Calibration 20
4.8.2 Sample rate 20
4.8.3 Background noise 21
4.8.4 Measurement points 21
4.8.5 Adrienne temporal window 21
4.8.6 Placement of the Adrienne temporal window 22
4.8.7 Low frequency limit and sample size 23
4.9 Positioning of the measuring equipment 24
4.9.1 Selection of the measurement positions 24
4.9.2 Reflecting objects 24
4.9.3 Safety considerations 25
4.10 Sound diffraction index difference 25
4.11 Single-number rating of sound diffraction index difference DLDI 25
4.12 Sample surface and meteorological conditions 26
4.12.1 Condition of the sample surface 26
4.12.2 Wind 26
4.12.3 Air temperature 26

5 Measurement uncertainty 26

6 Measuring procedure 26
6.1 General 26
6.2 Test report 27

Annex A (informative) Indoor measurements for product qualification 29

A.1 General 29
A.2 Parasitic reflections 29
A.3 Reverberation time of the room 29

Annex B (informative) Measurement uncertainty 30

B.1 General 30
B.2 Expression for the calculation of sound diffraction index 30
B.3 Contributions to measurement uncertainty 31
B.4 Expanded uncertainty of measurement 32
B.5 Measurement uncertainty based upon reproducibility data 32

Bibliography 33