DIN EN 12101-2:2017-08 (E)

Smoke and heat control systems - Part 2: Natural smoke and heat exhaust ventilators

Contents

Page

European foreword 5

Introduction 6

1 Scope 7

2 Normative references 7

3 Terms, definitions, symbols and abbreviations 7
3.1 Terms and definitions 7
3.2 Symbols and abbreviations 11

4 Requirements 13
4.1 Nominal activation conditions/sensitivity 13
4.1.1 Initiation device 13
4.1.2 Opening mechanism 14
4.1.3 Inputs and outputs 14
4.2 Response delay (response time) 14
4.2.1 Reliability 14
4.2.2 Opening under (snow/wind) load 14
4.2.3 Low ambient temperature 15
4.2.4 Opening under heat 15
4.3 Operational reliability 15
4.4 Effectiveness of smoke/hot gas extraction (aerodynamic free area) 15
4.5 Performance parameters under fire conditions 15
4.5.1 Resistance to heat 15
4.5.2 Mechanical stability 16
4.5.3 Reaction to fire 16
4.6 Performance under environmental conditions 16
4.6.1 Opening under load 16
4.6.2 Low ambient temperature 16
4.6.3 Stability under wind load 16
4.6.4 Resistance to wind-induced vibration 16
4.6.5 Resistance to heat 16
4.7 Durability 17
4.7.1 Response delay (response time) 17
4.7.2 Operational reliability 17
4.7.3 Performance parameters under fire conditions 17

5 Testing, assessment and sampling methods 17

6 Assessment and verification of constancy of performance - AVCP 19
6.1 General 19
6.2 Type Testing 19
6.2.1 General 19
6.2.2 Test samples, testing and compliance criteria 20
6.2.3 Test sequence 21
6.2.4 Test reports 22
6.2.5 Cascading determination of the product type results 22
6.3 Factory production control 23
6.3.1 General 23
6.3.2 Requirements 23

6.3.3 NSHEV specific requirements 25
6.3.4 Initial inspection of factory and FPC 26
6.3.5 Continuous surveillance of FPC 26
6.3.6 Procedure for modifications 27
6.3.7 Pre-production prototypes 27

7 Marking, labelling and packaging 28

Annex A (normative) Classification 29

A.1 Nominal activation condition/sensitivity 29
A.2 Response delay 29
A.3 Operational Reliability 29
A.4 Effectiveness of smoke/hot gas extraction (aerodynamic free area) 29
A.5 Performance parameters under fire conditions 29
A.6 Performance under environmental conditions 30
A.7 Durability 31
A.7.1 Response delay (response time) 31
A.7.2 Operational reliability 31
A.7.3 Performance parameters under fire conditions 31

Annex B (normative) Effectiveness of smoke/hot gas extraction (aerodynamic free area) 32

B.1 Determination of the aerodynamic free area 32
B.2 Simple assessment procedure 32
B.2.1 General 32
B.2.2 Roof mounted NSHEV 32
B.2.3 Wall mounted NSHEV 32
B.3 Experimental procedure 33
B.3.1 General 33
B.3.2 Test apparatus 33
B.3.3 Test specimen 34
B.3.4 Test procedure 35
B.3.5 Evaluation of test results 36
B.3.6 Calculation of the coefficient of discharge for a family of NSHEV 37
B.4 Test to check the aerodynamic test installations 38
B.4.1 General 38
B.4.2 Reference test without side wind 39
B.4.3 Reference tests with side wind 39
B.4.4 Evaluation of test results 39

Annex C (normative) Test method for operational reliability and response time 54

C.1 Objective of test 54
C.2 Test conditions 54
C.3 Test apparatus 54
C.4 Test specimen 54
C.5 Test procedure 54

Annex D (normative) Test method for opening under load 56

D.1 Objective of test 56
D.2 Test conditions 56
D.3 Test apparatus 56
D.4 Test specimen 57
D.5 Test procedure 57

Annex E (normative) Test method for low ambient temperature 58

E.1 Objective of test 58
E.2 Test apparatus 58
E.3 Test specimen 58

E.4 Test procedure 58

Annex F (normative) Test method for stability under wind load 59

F.1 Objective of test 59
F.2 Test conditions 59
F.3 Test apparatus 59
F.4 Test specimen 59
F.5 Test procedure 60
F.5.1 Wind load 60
F.5.2 Vibration 60

Annex G (normative) Test method for resistance to heat 61

G.1 Objective of the test 61
G.2 Test apparatus 61
G.2.1 Test furnace 61
G.2.2 Temperature measurement 61
G.2.3 NSHEV mount 61
G.3 Test specimen 62
G.3.1 General 62
G.3.2 NSHEV mounted to a glazed partition construction 62
G.3.3 Roof mounted NSHEV as part of a continuous rooflight 62
G.3.4 Wall mounted NSHEV 63
G.3.5 Roof mounted NSHEV 63
G.4 Test procedure 64

Annex H (normative) Mounting and fixing conditions for the SBI or small flame tests 72

H.1 General 72
H.2 Class E 73
H.2.1 General 73
H.2.2 Small flame test in accordance to EN ISO 11925-2 73
H.3 Class A2 to class D 73
H.3.1 General 73
H.3.2 Single Burning Item test (SBI) 74
H.4 Heat of combustion test 74

Annex I (normative) Handling changes affecting declared performances for NSHEV 75

I.1 General 75
I.2 Effectiveness of smoke/hot gas extraction 75
I.3 Reliability 75
I.4 Opening under load 76
I.5 Opening at low ambient temperatures 76
I.6 Wind load 77
I.7 Resistance to heat 77

Annex J (informative) Installation and maintenance information 78

J.1 Installation information 78
J.2 Maintenance information 78

Bibliography 88