

DIN EN 13637:2015-12 (E)

Building hardware - Electrically controlled exit systems for use on escape routes - Requirements and test methods

Contents		Page
Foreword		6
Introduction		7
1	Scope	8
2	Normative references	9
3	Terms and definitions	10
4	Requirements	13
4.1	General	13
4.1.1	Compliance	13
4.1.2	Association between components	13
4.1.3	Access level	14
4.2	Ability to release (for doors on escape routes)	14
4.2.1	Number of operations to release	14
4.2.2	Operation of initiating element	14
4.2.3	Input signal from an alarm system	15
4.2.4	Resetting conditions	15
4.2.5	Operating element	16
4.2.6	Fail safe function and reliability of liaison and transmission paths	17
4.2.7	Release force - Door not under pressure	19
4.2.8	Release force - Door under pressure	19
4.2.9	Release from the Initiating element	19
4.2.10	Release after power supply failure	19
4.2.11	Dimensional and design	20
4.2.12	Door mass and door dimensions	22
4.2.13	Keepers	23
4.2.14	Initiating element with cover	23
4.2.15	Finger trapping	23
4.2.16	Pictogram	23
4.2.17	Time delay	24
4.2.18	Central Management Control	25
4.2.19	Outside access device	30
4.2.20	Security requirements	30
4.3	Self-closing ability C (for fire/smoke doors)	31
4.4	Suitability for use on fire and smoke doors	32
4.5	Control of Dangerous substances	33
4.6	Durability of ability to release (against ageing and degradation for doors on escape routes)	33
4.6.1	General	33
4.6.2	Abuse resistance of electrical locking element	34
4.6.3	Abuse resistance of initiating element	34
4.6.4	Abuse resistance of electrically lockable operating element	34
4.6.5	Environmental requirements - Temperature range requirement	34
4.6.6	Environmental requirements - Corrosion resistance requirement	35
4.6.7	Environmental requirements - Dry Heat resistance requirement	35
4.6.8	Environmental requirements - Cold resistance requirement	35
4.6.9	Environmental requirements - Damp heat cyclic (12h + 12h) resistance requirement	36
4.6.10	Environmental requirements - Impact resistance requirement	36

4.6.11	Environmental requirements - Rated voltage requirements	38
4.6.12	Electrical hazards safety requirements (Low voltage)	39
4.6.13	Environmental requirements - Electromagnetic compatibility (EMC) requirements and/or Radio and telecommunication terminal equipment (R&TTE)	39
4.6.14	Environmental requirements - IP Protection against solid foreign objects and ingress of water and dust	41
4.7	Durability of self-closing ability C against ageing and degradation (for fire/smoke doors)	41
5	Testing, assessment and sampling methods	42
5.1	General	42
5.1.1	Test methods	42
5.1.2	Test apparatus	43
5.1.3	Procedures	44
5.2	Tests for Ability to Release	44
5.2.1	Test for number of operations to release	44
5.2.2	Test for operation of initiating element	45
5.2.3	Release function test - Input signal from the Alarm system such as an alarm system (sample A)	45
5.2.4	Tests for resetting conditions	47
5.2.5	Test for operating element	47
5.2.6	Test of fail safe function and failure of liaison and transmission paths, and release force test of initiating element (Sample A)	47
5.2.7	Release force test - Door not under pressure (Sample A)	48
5.2.8	Release force test - Door under pressure (Sample A)	49
5.2.9	Release from the Initiating element	50
5.2.10	Release tests after power supply failure (Sample A)	50
5.2.11	Verification of dimensions and design	50
5.2.12	Verification of Door mass and door dimensions	50
5.2.13	Verification of keepers	51
5.2.14	Verification of Initiating element with cover	51
5.2.15	Test for finger trapping	51
5.2.16	Verification of pictograms	51
5.2.17	Release test according to time delay (Sample A)	51
5.2.18	Central Management Control Tests	53
5.2.19	Outside Access Device	60
5.2.20	Security tests (Sample A)	60
5.3	Tests for self-closing ability C (Sample A)	62
5.4	Tests for Suitability for use on fire and smoke doors (Samples D and E)	63
5.5	Control of Dangerous substances	63
5.6	Tests for the Durability of ability to release and ability to self-closing (Sample A)	63
5.6.1	General	63
5.6.2	Abuse resistance test of electrical locking element	64
5.6.3	Abuse resistance test of initiating element	64
5.6.4	Abuse resistance of electrically lockable operating element	65
5.6.5	Temperature test (Sample B)	66
5.6.6	Corrosion test (Sample B)	66
5.6.7	Dry heat test (Sample B)	67
5.6.8	Cold test (Sample B)	68
5.6.9	Damp heat cyclic test (12h + 12h) (Sample B)	68
5.6.10	Impact test (Sample B)	69
5.6.11	Supply voltage variations test (Sample B)	71
5.6.12	Electrical hazards safety tests (Sample B)	72
5.6.13	Electromagnetic compatibility (EMC) tests (Sample B)	72
5.6.14	(IP)Protection against solid foreign objects and ingress of water and dust test (Sample B)	72
5.7	Tests for the Durability of ability to self-closing (Sample A)	72
6	Assessment and verification of constancy of performance - AVCP	73
6.1	General	73
6.2	Type testing	73

6.2.1	General	73
6.2.2	Test samples, testing and compliance criteria	74
6.2.3	Test reports	74
6.3	Factory production control (FPC)	74
6.3.1	General	74
6.3.2	Requirements	75
6.3.3	Product specific requirements	80
6.3.4	Initial inspection of factory and of FPC	81
6.3.5	Continuous surveillance of FPC	81
6.3.6	Procedure for modifications	82
7	Classification and designation	82
7.1	General	82
7.2	Classification system	82
7.2.1	General	82
7.2.2	Category of use (1st character)	82
7.2.3	Durability (2nd character)	82
7.2.4	Door mass (3rd character)	82
7.2.5	Suitability for use on fire/smoke doors (4th character)	83
7.2.6	Safety (5th character)	83
7.2.7	Corrosion resistance, humidity and IP protection (6th character)	83
7.2.8	Security/Holding force - from outside (7th character)	84
7.2.9	Security/Holding force - from inside (8th character)	84
7.2.10	Time delay (9th character)	85
7.2.11	Denied exit mode (10th character)	85
7.2.12	Configuration (11th character)	85
7.3	Example of classification	85
8	Marking, labelling and packaging	86
8.1	On the product	86
8.2	On the packaging	86
8.3	On the installation instructions	87
Annex A (informative) Information supplied with the product		88
A.1	General	88
A.2	Product information	89
A.3	Installation and fixing instructions	90
A.3.1	Fixing arrangements	90
A.3.2	Information and installation guidance	90
A.4	Installation compliance report form	93
A.5	Maintenance instructions	96
A.6	Routine site inspection report form	96
Annex B (normative) Test sequences with different samples		98
Annex C (informative) Guidance for choosing relevant product standards for particular exit door applications		100
Annex D (informative) Access levels, Installation and maintenance		102
D.1	Access levels	102
D.1.1	Definitions	102
D.1.2	Access levels for typical operations on the electrically controlled exit system	103
D.1.3	Installation	103
D.1.4	Maintenance	104
D.2	Advantages/disadvantages of panic and emergency exit devices and systems	104
D.2.1	Design of operating elements	104
D.2.2	Design of outside access device	104
D.2.3	Low operating forces	104
D.2.4	Bottom vertical rods and projecting floor sockets	105

D.2.5	Automatic locking	105
D.2.6	Dogging mechanism	105
D.2.7	Electrically controlled functions	105
D.2.8	Projection of the exit device	105
D.2.9	Recognition of operating element	106
D.3	Operating forces declared by the manufacturer	106
D.3.1	General	106
D.3.2	Performance assessment	106
D.3.3	Test methods - Operating tests under side load	106
D.3.4	Manufacturer's declaration	107
Annex E (informative) Functional diagrams		108
E.1	Functional diagrams of typical electrically controlled exit systems	108
E.2	Logic diagram for modes of exit system operation	109
Annex F (informative) Examples of configurations and description of exit systems		110
F.1	Configuration of exit system	110
F.2	Description of exit systems	113
F.3	Door configurations	114
Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation		115
ZA.1	Scope and relevant characteristics	115
ZA.2	Procedure for AVCP of Electrically controlled exit systems	117
ZA.2.1	System of AVCP	117
ZA.2.2	Declaration of performance (DoP)	118
ZA.2.2.1	General	118
ZA.2.2.2	Content	118
ZA.2.3	Example of DoP	119
ZA.3	CE marking and labelling	123