

# DIN 4093:2015-11 (E)

## Design of strengthened soil - Set up by means of jet grouting, deep mixing or grouting

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Terms and definitions and symbols .....</b>	<b>5</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>5</b>
<b>3.2</b>	<b>Symbols .....</b>	<b>6</b>
<b>4</b>	<b>Soil solidification .....</b>	<b>7</b>
<b>4.1</b>	<b>General requirements .....</b>	<b>7</b>
<b>4.2</b>	<b>Classification into geotechnical categories .....</b>	<b>8</b>
<b>4.3</b>	<b>Action and effects of actions .....</b>	<b>8</b>
<b>4.3.1</b>	<b>General .....</b>	<b>8</b>
<b>4.3.2</b>	<b>Actions specific to foundation engineering .....</b>	<b>9</b>
<b>4.3.3</b>	<b>Dynamic actions .....</b>	<b>9</b>
<b>4.3.4</b>	<b>Characteristic effects of actions .....</b>	<b>9</b>
<b>4.3.5</b>	<b>Design values of effects of actions .....</b>	<b>9</b>
<b>4.4</b>	<b>Resistances .....</b>	<b>9</b>
<b>4.4.1</b>	<b>General .....</b>	<b>9</b>
<b>4.4.2</b>	<b>Characteristic strength .....</b>	<b>9</b>
<b>4.4.3</b>	<b>Deformation behaviour .....</b>	<b>11</b>
<b>4.4.4</b>	<b>Design value of strength .....</b>	<b>11</b>
<b>4.4.5</b>	<b>Anchoring in jet grouted slabs .....</b>	<b>12</b>
<b>4.4.6</b>	<b>Geometrical dimensions of solidified soil .....</b>	<b>13</b>
<b>4.5</b>	<b>Durability .....</b>	<b>14</b>
<b>4.6</b>	<b>Bearing capacity verification .....</b>	<b>14</b>
<b>4.7</b>	<b>Serviceability verification .....</b>	<b>14</b>
<b>4.8</b>	<b>Testing and controls .....</b>	<b>14</b>
	<b>Annex A (normative) Strength testing .....</b>	<b>15</b>
	<b>Annex B (normative) Creep testing .....</b>	<b>16</b>
<b>B.1</b>	<b>General .....</b>	<b>16</b>
<b>B.2</b>	<b>Soil solidification with cement .....</b>	<b>16</b>
<b>B.3</b>	<b>Soil solidification with silica gel .....</b>	<b>17</b>