

DIN EN 14305:2016-03 (E)

Thermal insulation products for building equipment and industrial installations - Factory made cellular glass (CG) products - Specification

| Contents | | Page |
|-------------------------|---|-------------|
| European foreword | | 4 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 8 |
| 3.1 | Terms and definitions | 8 |
| 3.1.1 | Terms and definitions as given in EN ISO 9229:2007 | 8 |
| 3.1.2 | Additional terms and definitions | 9 |
| 3.2 | Symbols, units and abbreviated terms | 9 |
| 3.2.1 | Symbols and units used in this standard | 9 |
| 3.2.2 | Abbreviated terms used in this standard | 11 |
| 4 | Requirements | 11 |
| 4.1 | General | 11 |
| 4.2 | For all applications | 11 |
| 4.2.1 | Thermal conductivity | 11 |
| 4.2.2 | Dimensions and tolerances | 12 |
| 4.2.3 | Dimensional stability | 13 |
| 4.2.4 | Reaction to fire classification of the product as placed on the market | 13 |
| 4.2.5 | Durability characteristics | 14 |
| 4.3 | For specific applications | 14 |
| 4.3.1 | General | 14 |
| 4.3.2 | Maximum service temperature | 14 |
| 4.3.3 | Minimum service temperature | 15 |
| 4.3.4 | Compressive strength | 15 |
| 4.3.5 | Bending strength | 16 |
| 4.3.6 | Point load | 16 |
| 4.3.7 | Tensile strength parallel to faces | 16 |
| 4.3.8 | Tensile strength perpendicular to faces | 17 |
| 4.3.9 | Compressive creep | 17 |
| 4.3.10 | Water absorption | 17 |
| 4.3.11 | Water vapour diffusion resistance | 17 |
| 4.3.12 | Trace quantities of water soluble ions and the pH-value | 18 |
| 4.3.13 | Sound absorption | 18 |
| 4.3.14 | Release of dangerous substances | 18 |
| 4.3.15 | Continuous glowing combustion | 18 |
| 5 | Test methods | 18 |
| 5.1 | Sampling | 18 |
| 5.2 | Conditioning | 18 |
| 5.3 | Testing | 19 |
| 5.3.1 | General | 19 |
| 5.3.2 | Thermal conductivity | 19 |
| 5.3.3 | Reaction to fire | 21 |
| 6 | Designation code | 22 |
| 7 | Assessment and Verification of the Constancy of Performance (AVCP) | 22 |
| 7.1 | General | 22 |

| | | |
|--|---|----|
| 7.2 | Product Type Determination (PTD) | 23 |
| 7.3 | Factory Production Control (FPC) | 23 |
| 8 | Marking and labelling | 23 |
| Annex A (normative) Factory production control | | 24 |
| Annex B (normative) Determination of minimum service temperature | | 27 |
| B.1 | Definitions | 27 |
| B.2 | Principle | 27 |
| B.3 | Apparatus | 27 |
| B.4 | Test specimens | 28 |
| B.5 | Procedure | 28 |
| B.6 | Calculation and expression of results | 29 |
| B.7 | Accuracy of measurements | 29 |
| B.8 | Test report | 30 |
| Annex C (informative) Additional properties | | 31 |
| C.1 | General | 31 |
| C.2 | Fire protection | 31 |
| C.3 | Compressive strength | 31 |
| C.4 | Shear strength | 31 |
| C.5 | Dimensional stability under constant normal laboratory conditions | 31 |
| C.6 | Coefficient of thermal expansion | 32 |
| C.7 | Apparent density | 32 |
| Annex D (informative) Preparation of the flat test specimens to measure thermal conductivity | | 33 |
| D.1 | Introduction | 33 |
| D.2 | Procedure to get flat test specimen faces: method of the three rulers | 33 |
| Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation | | 34 |
| ZA.1 Scope and relevant characteristic | | 34 |
| ZA.2 Procedures for AVCP of factory made cellular glass products | | 35 |
| ZA.3 CE Marking and labelling | | 43 |
| Bibliography | | 45 |