

DIN EN 14307:2016-03 (E)

Thermal insulation products for building equipment and industrial installations - Factory made extruded polystyrene foam (XPS) products - Specification

Contents		Page
European foreword		4
1	Scope	6
2	Normative references	6
3	Terms, definitions, symbols, units and abbreviated terms	8
3.1	Terms and definitions	8
3.1.1	Terms and definitions as given in EN ISO 9229:2007	8
3.1.2	Additional terms and definitions	8
3.2	Symbols, units and abbreviated terms	9
3.2.1	Symbols and units used in this standard	9
3.2.2	Abbreviations used in this standard	10
4	Requirements	10
4.1	General	10
4.2	For all applications	11
4.2.1	Thermal conductivity	11
4.2.2	Dimensions and tolerances	11
4.2.3	Dimensional stability	12
4.2.4	Reaction to fire of the product as placed on the market	13
4.2.5	Durability characteristics	13
4.3	For specific applications	13
4.3.1	General	13
4.3.2	Maximum service temperature	13
4.3.3	Minimum service temperature	14
4.3.4	Compressive stress or compressive strength	14
4.3.5	Water vapour diffusion transmission properties	14
4.3.6	Short-term water absorption by partial immersion	15
4.3.7	Trace quantities of water soluble ions and the pH-value	15
4.3.8	Release of dangerous substances	15
4.3.9	Continuous glowing combustion	15
5	Test methods	15
5.1	Sampling	15
5.2	Conditioning	15
5.3	Testing	15
5.3.1	General	15
5.3.2	Thermal conductivity	16
5.3.3	Reaction to fire	16
6	Designation code	18
7	Assessment and Verification of the Constancy of Performance (AVCP)	18
7.1	General	18
7.2	Product Type Determination (PTD)	18
7.3	Factory Production Control (FPC)	19
8	Marking and labelling	19
Annex A (normative) Factory production control		20

Annex B (normative) Determination of the aged values of thermal conductivity	22
B.1 Scope	22
B.2 Procedure for XPS foam without diffusion tight laminates	22
B.3 Procedure for XPS foam for use with diffusion tight facings on both sides	23
B.4 Blowing agent	23
Annex C (informative) Additional properties	24
C.1 General	24
C.2 Behaviour under cyclic loading	24
C.3 Compressive modulus of elasticity	24
C.4 Bending strength	24
C.5 Shear strength	24
C.6 Deformation under specified compressive load and temperature conditions	25
C.7 Compressive creep	25
C.8 Tensile strength perpendicular to facings	26
C.9 Long term water absorption by diffusion	26
C.10 Long term water absorption by immersion	26
C.11 Freeze-thaw resistance	27
C.12 Apparent density	27
C.13 Coefficient of thermal expansion	27
C.14 Closed cell content	27
Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation	29
ZA.1 Scope and relevant characteristics	29
ZA.2 Procedures for AVCP of factory made extruded polystyrene foam products	31
ZA.3 CE Marking and labelling	38
Bibliography	40