

# DIN EN 14309:2016-03 (E)

## Thermal insulation products for building equipment and industrial installations - Factory made products of expanded polystyrene (EPS) - Specification

---

| <b>Contents</b>         |  | <b>Page</b> |
|-------------------------|--|-------------|
| European foreword ..... |  | 4           |
| <b>1</b>                | <b>Scope .....</b>   | <b>6</b>    |
| <b>2</b>                | <b>Normative references .....</b>  | <b>6</b>    |
| <b>3</b>                | <b>Terms, definitions, symbols, units and abbreviated terms .....</b>                  | <b>8</b>    |
| <b>3.1</b>              | <b>Terms and definitions .....</b>   | <b>8</b>    |
| <b>3.1.1</b>            | <b>Terms and definitions as given in EN ISO 9229:2007 .....</b>                        | <b>8</b>    |
| <b>3.1.2</b>            | <b>Additional terms and definitions .....</b>  | <b>9</b>    |
| <b>3.2</b>              | <b>Symbols, units and abbreviated terms .....</b>                                      | <b>10</b>   |
| <b>3.2.1</b>            | <b>Symbols and units used in this standard .....</b>                                   | <b>10</b>   |
| <b>3.2.2</b>            | <b>Abbreviated terms used in this standard .....</b>                                   | <b>12</b>   |
| <b>4</b>                | <b>Requirements .....</b>  | <b>12</b>   |
| <b>4.1</b>              | <b>General .....</b>   | <b>12</b>   |
| <b>4.2</b>              | <b>For all applications .....</b>  | <b>12</b>   |
| <b>4.2.1</b>            | <b>Thermal conductivity .....</b>  | <b>12</b>   |
| <b>4.2.2</b>            | <b>Dimensions and tolerances .....</b>   | <b>13</b>   |
| <b>4.2.3</b>            | <b>Dimensional stability .....</b>   | <b>13</b>   |
| <b>4.2.4</b>            | <b>Reaction to fire of the product as placed on the market .....</b>                   | <b>14</b>   |
| <b>4.2.5</b>            | <b>Durability characteristics .....</b>  | <b>14</b>   |
| <b>4.3</b>              | <b>For specific applications .....</b>   | <b>15</b>   |
| <b>4.3.1</b>            | <b>General .....</b>   | <b>15</b>   |
| <b>4.3.2</b>            | <b>Maximum service temperature .....</b>   | <b>15</b>   |
| <b>4.3.3</b>            | <b>Minimum service temperature .....</b>   | <b>15</b>   |
| <b>4.3.4</b>            | <b>Dimensional stability under specified temperature and humidity conditions .....</b> | <b>15</b>   |
| <b>4.3.5</b>            | <b>Compressive stress at 10 % deformation .....</b>                                    | <b>15</b>   |
| <b>4.3.6</b>            | <b>Tensile strength perpendicular to faces .....</b>                                   | <b>16</b>   |
| <b>4.3.7</b>            | <b>Bending strength .....</b>  | <b>16</b>   |
| <b>4.3.8</b>            | <b>Compressive creep .....</b>   | <b>17</b>   |
| <b>4.3.9</b>            | <b>Water absorption .....</b>  | <b>18</b>   |
| <b>4.3.10</b>           | <b>Water vapour transmission .....</b>   | <b>18</b>   |
| <b>4.3.11</b>           | <b>Apparent density .....</b>  | <b>19</b>   |
| <b>4.3.12</b>           | <b>Dynamic stiffness .....</b>   | <b>19</b>   |
| <b>4.3.13</b>           | <b>Compressibility .....</b>   | <b>19</b>   |
| <b>4.3.14</b>           | <b>Trace quantities of water soluble ions and pH .....</b>                             | <b>20</b>   |
| <b>4.3.15</b>           | <b>Release of dangerous substances .....</b>   | <b>20</b>   |
| <b>4.3.16</b>           | <b>Continuous glowing combustion .....</b>   | <b>21</b>   |
| <b>5</b>                | <b>Test methods .....</b>  | <b>21</b>   |
| <b>5.1</b>              | <b>Sampling .....</b>  | <b>21</b>   |
| <b>5.2</b>              | <b>Conditioning .....</b>  | <b>21</b>   |
| <b>5.3</b>              | <b>Testing .....</b>   | <b>21</b>   |
| <b>5.3.1</b>            | <b>General .....</b>   | <b>21</b>   |
| <b>5.3.2</b>            | <b>Thermal conductivity .....</b>  | <b>23</b>   |
| <b>5.3.3</b>            | <b>Reaction to fire .....</b>  | <b>24</b>   |
| <b>6</b>                | <b>Designation code .....</b>  | <b>24</b>   |
| <b>7</b>                | <b>Assessment and Verification of the Constancy of Performance (AVCP) .....</b>        | <b>25</b>   |

|  |  |    |
|--|--|----|
| 7.1  | General .....  | 25 |
| 7.2  | Product Type Determination (PTD) .....   | 25 |
| 7.3  | Factory Production Control (FPC) .....   | 25 |
| 8  | Marking and labelling .....  | 26 |
| Annex A (normative) Factory production control .....   |  | 27 |
| A.1  | Indirect testing .....   | 30 |
| Annex B (normative) Product classification .....   |  | 34 |
| Annex C (normative) Determination of minimum service temperature .....   |  | 35 |
| C.1  | Definitions .....  | 35 |
| C.2  | Principle .....  | 35 |
| C.3  | Apparatus .....  | 35 |
| C.4  | Test specimens .....   | 35 |
| C.5  | Procedure .....  | 36 |
| C.6  | Calculation and expression of results .....                                      | 36 |
| C.7  | Accuracy of measurements .....   | 37 |
| C.8  | Test report .....  | 37 |
| Annex D (informative) Additional properties .....  |  | 39 |
| D.1  | General .....  | 39 |
| D.2  | Long-term compressive behaviour .....  | 39 |
| D.3  | Shear behaviour .....  | 39 |
| D.4  | Water vapour diffusion resistance factor .....                                   | 40 |
| D.5  | Coefficient of thermal expansion .....   | 40 |
| D.6  | Behaviour under cyclic loading .....   | 40 |
| D.7  | Test methods .....   | 41 |
| D.8  | Additional information .....   | 41 |
| Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU<br>Construction Products Regulation ..... |  | 42 |
| ZA.1   | Scope and relevant characteristics .....   | 42 |
| ZA.2   | Procedures for AVCP of factory made products of expanded polystyrene (EPS) ..... | 44 |
| ZA.3   | CE Marking and labelling .....   | 51 |
| Bibliography .....   |  | 53 |