

DIN EN 14314:2016-03 (E)

Thermal insulation products for building equipment and industrial installations - Factory made phenolic foam (PF) products - Specification

| Contents | | Page |
|-------------------------|---|-------------|
| European foreword | | 4 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms, definitions, symbols, units and abbreviated terms | 8 |
| 3.1 | Terms and definitions | 8 |
| 3.1.1 | Terms and definitions as given in EN ISO 9229 | 8 |
| 3.1.2 | Additional terms and definitions | 8 |
| 3.2 | Symbols, units and abbreviated terms | 9 |
| 3.2.1 | Symbols and units used in this standard | 9 |
| 3.2.2 | Abbreviated terms used in this standard | 10 |
| 4 | Requirements | 11 |
| 4.1 | General | 11 |
| 4.2 | For all applications | 11 |
| 4.2.1 | Thermal conductivity | 11 |
| 4.2.2 | Dimensions and tolerances | 11 |
| 4.2.3 | Dimensional stability | 13 |
| 4.2.4 | Reaction to fire of the product as placed on the market | 13 |
| 4.2.5 | Durability characteristics | 13 |
| 4.3 | For specific applications | 14 |
| 4.3.1 | General | 14 |
| 4.3.2 | Maximum service temperature | 14 |
| 4.3.3 | Minimum service temperature | 14 |
| 4.3.4 | Dimensional stability under specified conditions | 14 |
| 4.3.5 | Compression resistance properties | 15 |
| 4.3.6 | Water vapour diffusion resistance | 16 |
| 4.3.7 | Water absorption | 16 |
| 4.3.8 | Closed cell content | 17 |
| 4.3.9 | Trace quantities of water soluble chloride and the pH-value | 17 |
| 4.3.10 | Release of dangerous substances | 17 |
| 4.3.11 | Continuous glowing combustion | 17 |
| 5 | Test methods | 18 |
| 5.1 | Sampling | 18 |
| 5.2 | Conditioning | 18 |
| 5.3 | Testing | 18 |
| 5.3.1 | General | 18 |
| 5.3.2 | Thermal conductivity | 20 |
| 5.3.3 | Reaction to Fire | 21 |
| 6 | Designation code | 21 |
| 7 | Assessment and Verification of the Constancy of Performance (AVCP) | 21 |
| 7.1 | General | 21 |
| 7.2 | Product Type Determination (PTD) | 22 |
| 7.3 | Factory Production Control (FPC) | 22 |
| 8 | Marking and labelling | 22 |

| | |
|--|-----------|
| Annex A (normative) Factory production control | 23 |
| Annex B (normative) Determination of the aged value of thermal conductivity | 25 |
| B.1 General | 25 |
| B.2 Preparation of test sample | 25 |
| B.3 Determination of the initial value of thermal conductivity | 26 |
| B.4 Determination of the aged value of thermal conductivity | 26 |
| B.5 Blowing agent | 27 |
| B.6 Declaration of thermal resistance and thermal conductivity | 27 |
| Annex C (normative) Determination of minimum service temperature | 28 |
| C.1 Definitions | 28 |
| C.2 Principle | 28 |
| C.3 Apparatus | 28 |
| C.4 Test specimens | 29 |
| C.5 Procedure | 29 |
| C.6 Calculation and expression of results | 30 |
| C.7 Accuracy of measurements | 30 |
| C.8 Test report | 30 |
| C.9 Modifications of and additions to the general test method for phenolic foams | 31 |
| Annex D (informative) Additional properties | 34 |
| D.1 General | 34 |
| D.2 Apparent density | 34 |
| D.3 Coefficient of thermal expansion | 34 |
| D.4 Water vapour transmission of preformed pipe insulation | 34 |
| D.5 Tensile strength perpendicular to faces | 34 |
| D.6 Shear strength | 34 |
| D.7 Bending strength | 35 |
| D.8 Cell gas composition | 35 |
| D.9 Cryogenic application | 35 |
| Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation | 36 |
| ZA.1 Scope and relevant characteristics | 36 |
| ZA.2 Procedures for AVCP of factory made phenolic foam | 38 |
| ZA.3 CE Marking and labelling | 45 |
| Bibliography | 47 |