

DIN EN 15681-1:2016-06 (E)

Glass in building - Basic alumino silicate glass products - Part 1: Definitions and general physical and mechanical properties

| Contents | | Page |
|---|--|-------------|
| European foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms and definitions | 4 |
| 4 | Chemical composition | 6 |
| 4.1 | General | 6 |
| 4.2 | Tint | 6 |
| 5 | Physical and mechanical characteristics | 6 |
| 5.1 | General characteristics | 6 |
| 5.2 | Characteristic bending strength | 7 |
| 5.3 | Designation of clear alumino silicate glass | 7 |
| 5.3.1 | General | 7 |
| 5.3.2 | Clear transparent alumino silicate glass | 8 |
| 5.3.3 | Clear translucent alumino silicate glass | 8 |
| 5.4 | Stability of physical and chemical characteristics | 9 |
| 6 | Dimensional requirements | 9 |
| 6.1 | Manufacturing dimensions | 9 |
| 6.1.1 | Stock sizes | 9 |
| 6.1.2 | Supplied and final cut sizes | 9 |
| 6.2 | Thickness and thickness tolerances | 9 |
| 6.3 | Length, width and squareness | 10 |
| 7 | Quality requirements | 10 |
| 7.1 | General | 10 |
| 7.2 | Methods of observation and measurement | 11 |
| 7.2.1 | Optical faults | 11 |
| 7.2.2 | Visual faults (spot faults, linear/extended faults), all types of basic alumino silicate glass | 12 |
| 7.3 | Acceptance levels | 13 |
| 7.3.1 | Optical faults | 13 |
| 7.3.2 | Visual faults (spot faults, linear/extended faults), all types of basic alumino silicate glass | 13 |
| 7.4 | Edge defects for final cut sizes | 14 |
| 7.4.1 | Entrant and emergent faults | 14 |
| 7.4.2 | Bevel | 14 |
| 7.4.3 | Limitations on edge defects | 14 |
| 8 | Designation | 15 |
| Annex A (informative) Complementary information related to REACH | | 16 |
| Bibliography | | 17 |