

ISO 1288-1:2016-02 (E)

Glass in building - Determination of the bending strength of glass - Part 1: Fundamentals of testing glass

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Symbols | 2 |
| 5 | Factors to be taken into account when testing glass | 3 |
| 5.1 | Glass as a material | 3 |
| 5.1.1 | General | 3 |
| 5.1.2 | Effect of surface condition | 4 |
| 5.1.3 | Effect of rate of loading | 4 |
| 5.1.4 | Effect of test surface area | 4 |
| 5.1.5 | Effect of ambient medium | 5 |
| 5.1.6 | Effect of aging | 5 |
| 5.1.7 | Effect of temperature | 5 |
| 5.2 | Bending stress and bending strength | 5 |
| 5.2.1 | General | 5 |
| 5.2.2 | Effective stress | 5 |
| 5.2.3 | Equivalent bending strength | 6 |
| 5.2.4 | Profile bending strength | 6 |
| 5.3 | Types of glass | 6 |
| 5.3.1 | General | 6 |
| 5.3.2 | Patterned glass | 6 |
| 5.3.3 | Laminated glass | 6 |
| 5.4 | Orientation of the specimens | 7 |
| 5.5 | Number of specimens in a sample | 7 |
| 6 | Explanations of the test methods | 7 |
| 6.1 | Coaxial double ring test for large test surface areas | 7 |
| 6.1.1 | Elimination of edge effects | 7 |
| 6.1.2 | Analysis of the stress development | 7 |
| 6.1.3 | Testing of patterned glass | 11 |
| 6.2 | Test with specimen supported at two points (four point bending) | 11 |
| 6.1.4 | Limitations | 11 |
| 6.1.5 | Inclusion of edge effects | 11 |
| 6.1.6 | Analysis of the stress development | 11 |
| 6.3 | Coaxial double ring test for small test surface areas | 13 |
| 6.1.7 | Elimination of edge effects | 13 |
| 6.1.8 | Analysis of the stress development | 13 |
| 7 | Range of application of the test methods | 14 |
| 7.1 | General limitations | 14 |
| 8 | Calibration of the testing machines | 15 |
| 9 | Recommendations for safe use of test equipment | 15 |
| Bibliography | | 17 |