ISO 1288-2:2016-02 (E)

Glass in building - Determination of the bending strength of glass - Part 2: Coaxial double-ring test on flat specimens with la rge test surface areas

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Symbols 2

5 Principle of test method 2

6 Apparatus 3
6.1 Testing machine 3
6.2 Loading device 4
6.2.1 Ring load 4
6.2.2 Surface pressure regulator 4
6.3 Measuring instruments 5

7 Sample 5
7.1 Shape and dimensions of the specimens 5
7.2 Sampling and preparation of specimens 5
7.2.1 Cutting and handling 5
7.2.2 Conditioning 5
7.2.3 Examination 6
7.2.4 Adhesive film 6
7.3 Number of specimens 6

8 Procedure 6
8.1 Temperature 6
8.2 Humidity 6
8.3 Thickness measurement 6
8.4 Base plate 6
8.5 Positioning of specimen and loading ring 6
8.6 Load application 7
8.7 Loading rate 7
8.8 Location of the origin 7
8.9 Assessment of residual stresses 7

9 Evaluation 8
9.1 Limitation of the evaluation 8
9.2 Calculation of bending strength 8

10 Test report 9

Annex A (informative) Example of a device for keeping the gas pressure, p, in line with the piston force, F 11

Bibliography 14