

# ISO 1288-2:2016-02 (E)

## Glass in building - Determination of the bending strength of glass - Part 2: Coaxial double-ring test on flat specimens with large test surface areas

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Symbols .....	2
5	Principle of test method .....	2
6	Apparatus .....	3
6.1	Testing machine .....	3
6.2	Loading device .....	4
6.2.1	Ring load .....	4
6.2.2	Surface pressure regulator .....	4
6.3	Measuring instruments .....	5
7	Sample .....	5
7.1	Shape and dimensions of the specimens .....	5
7.2	Sampling and preparation of specimens .....	5
7.2.1	Cutting and handling .....	5
7.2.2	Conditioning .....	5
7.2.3	Examination .....	6
7.2.4	Adhesive film .....	6
7.3	Number of specimens .....	6
8	Procedure .....	6
8.1	Temperature .....	6
8.2	Humidity .....	6
8.3	Thickness measurement .....	6
8.4	Base plate .....	6
8.5	Positioning of specimen and loading ring .....	6
8.6	Load application .....	7
8.7	Loading rate .....	7
8.8	Location of the origin .....	7
8.9	Assessment of residual stresses .....	7
9	Evaluation .....	8
9.1	Limitation of the evaluation .....	8
9.2	Calculation of bending strength .....	8
10	Test report .....	9
Annex A (informative)	Example of a device for keeping the gas pressure, $p$ , in line with the piston force, $F$ .....	11
Bibliography .....		14