

DIN EN 13166:2016-09 (E)

Thermal insulation products for buildings - Factory made phenolic foam (PF) products - Specification (includes Amendment :2016)

Contents		Page
European foreword		4
1	Scope	7
2	Normative references	7
3	Terms, definitions, symbols, units and abbreviated terms	9
4	Requirements	12
5	Test methods	19
6	Designation code	21
7	Assessment and Verification of the Constancy of Performance (AVCP)	22
8	Marking and labelling	22
Annex A (normative) Determination of the declared values of thermal resistance and thermal conductivity		24
A.1	General	24
A.2	Input data	24
A.3	Declared values	24
Annex B (normative) "Product type determination" ("PTD") and factory production control (FPC)		26
Annex C (normative) Determination of the aged values of thermal resistance and thermal conductivity		30
C.1	General	30
C.2	Preparation of test sample	31
C.3	Determination of the initial value of thermal conductivity	31
C.4	Determination of the aged value of thermal conductivity	31
C.5	Blowing agent	33
C.6	Declaration of thermal resistance and thermal conductivity	34
Annex D (informative) Additional properties		35
D.1	General	35
D.2	Shear strength	35
D.3	Cell gas composition	35
Annex E (normative) PF multi-layered thermal insulation products		36
E.1	General	36
E.2	Requirements	36
E.3	Test methods	37
E.4	Evaluation of conformity	37

Annex ZA (informative) "Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation"	38
Bibliography	49
Tables Table 1 -- Tolerances for length and width	13
Table 2 -- Classes for thickness tolerances	13
Table 3 -- Tolerances for deviation from flatness	14
Table 4 -- Dimensional stability under specified temperature and humidity conditions	15
Table 5 -- Levels for compressive strength	16
Table 6 -- Levels for tensile strength perpendicular to faces	16
Table 7 -- Levels for short term water absorption by partial immersion	17
Table 8 -- Levels for long term water absorption by partial immersion	17
Table 9 -- Test methods, specimens and conditions	20
Table A.1 -- Values for k for one side 90 % tolerance interval with a confidence level of 90 %	25
Table B.1 -- Minimum number of tests for "PTD" and minimum product testing frequencies	26
Table B.2 -- Minimum product testing frequencies for the reaction to fire characteristics	28
Table C.1 -- Test times for product thicknesses	32
Table C.2 -- Increments to be added to accelerated aged values of thermal conductivity to obtain the time averaged value over 25 years (W/mK)	33
Table D.1 -- Test methods, test specimens, conditions and minimum testing frequencies	35
Table ZA.1 -- Relevant clauses for factory made phenolic foam and intended use	39
Table ZA.2 -- Systems of AVCP	40
Table ZA.3.1 -- Assignment of AVCP tasks for factory made phenolic foam products under system 1 for reaction to fire and system 3 (see Table ZA.2)	41
Table ZA.3.2 -- Assignment of AVCP tasks for factory made phenolic foam products under system 3 (see Table ZA.2)	42
Table ZA.3.3 -- Assignment of AVCP tasks for factory made phenolic foam products under combined system 4 for reaction to fire and system 3 (see Table ZA.2)	43
Figures Figure ZA.1 -- "Example CE marking information of products under AVCP system 1 and system 3"	48