DIN EN 16809-2:2017-04 (E)

Therma l insulation products of buildings - In-situ formed products from loose-fill expanded polystyrene (EPS) beads and bonded expanded polystyrene beads - Part 2: Specification for the bonded and loose-fill products after installation

Contents

Page

European foreword 4

1 Scope 5

2 Normative references 5

3 Terms, definitions, symbols and abbreviations 5
3.1 Terms and definitions 5
3.2 Symbols and abbreviations 6

4 Requirements 6
4.1 General 6
4.2 Suitability of the building for the installation of the product 6
4.3 In situ measurements and calculations 6
4.3.1 General 6
4.3.2 The installed thermal resistance of masonry cavity wall and frame construction insulation 7

5 Installation checks 7
5.1 Average cavity width 7
5.2 Machine output 7
5.3 Installed volume 7
5.4 Thermal resistance of installed masonry cavity wall and frame construction installation 7

6 Guidelines for installation 8

7 Installer s declaration 8

Annex A (normative) Masonry cavity walls - Determination of average cavity width 9

A.1 Procedure 9
A.2 Calculation 9

Annex B (normative) Masonry cavity walls and frame constructions - Flow check procedures 10

B.1 Apparatus 10
B.2 Procedure 10

Annex C (normative) Masonry cavity walls - Use of endoscope to check adequacy of fill 11

C.1 Selection of inspection positions by the inspector 11
C.2 Action to be taken by the inspector 11

Annex D (normative) Guidance for the installer - Suitability of the building, training, pre- checks and installation declaration 12

D.1 Masonry cavity walls 12
D.1.1 Suitability of the building to receive the insulation 12
D.1.2 Suitability of the building to receive the insulation 12

D.1.3 Installation procedure 13

D.2 Frame constructions (new build walls) 13
D.2.1 Suitability of the building to receive the insulation 13
D.2.2 Control tests made by the installer when preparing the product on site 14
D.2.3 Installation procedure 14
D.2.4 An example of a declaration form for use by the installer 14

Bibliography 15