

ISO/TS 19700:2016-09 (E)

Controlled equivalence ratio method for the determination of hazardous components of fire effluents - Steady-state tube furnace

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	2
3	Terms and definitions	2
4	Principle	3
5	Apparatus	4
5.1	General apparatus	4
5.2	Tubular furnace	4
5.3	Calibrated thermocouples	6
5.4	Quartz furnace tube	6
5.5	Combustion boat	6
5.6	Combustion boat drive	7
5.6.1	Mechanism	7
5.6.2	Rate of specimen introduction	7
5.7	Mixing and measurement chamber	8
5.8	Analysis of gases	8
5.9	Determination of smoke aerosols	10
5.10	Exhaust system	10
6	Air supplies	10
6.1	Primary and secondary air supplies	10
6.2	Primary airflow calibration	10
6.3	Secondary airflow calibration	11
6.4	Overall confirmation	11
7	Establishment of furnace temperature and setting of furnace temperature	11
7.1	General	11
7.2	Establishing furnace temperature profile to determine furnace suitability	12
7.3	Setting the temperature for an individual test run condition	12
8	Test specimen preparation	13
8.1	Test specimen form	13
8.2	Combustible loading	13
8.3	Specimen conditioning	13
9	Selection of test decomposition conditions	13
9.1	Selection of decomposition conditions for fire hazard analysis or fire safety engineering13 9.2 Stage 1b): oxidative pyrolysis from externally applied radiation	14
9.3	Stage 2: well-ventilated flaming	14
9.4	Stage 3a): small vitiated fires in closed or poorly ventilated compartments	15
9.5	Stage 3b): post-flashover fires in open compartments	16
10	Procedure	16
10.1	Safety considerations	16

10.2	Decomposition of the test specimen	16
10.3	Steady-state period	18
10.4	Sampling and analysis of fire effluent	18
10.4.1	General	18
10.4.2	Sampling of fire effluent	18
10.4.3	Determination of the mass of the specimen residue	20
10.4.4	Ambient conditions	20
10.5	Validity of test run	21
11	Calculations	21
11.1	General	21
11.2	Mass-charge concentration and mass-loss concentration	21
11.2.1	Mass-charge concentration	21
11.2.2	Mass-loss concentration	21
11.3	Yield	22
11.4	Organic fraction	24
12	Test report	24
12.1	of test report	24
12.2	Test laboratory details	25
12.3	Specimen details	25
12.4	Test conditions and procedures	25
13	Verification of test apparatus with PMMA	26
13.1	Procedure	26
13.2	Verification criteria	26
14	Trueness and uncertainties with respect to steady-state tube furnace concentration and yields	26
14.1	Accuracy, trueness and uncertainty	26
14.2	Accuracy and trueness of concentration and yield measurements in the steady- state tube furnace (SSTF)	26
14.3	Extent of variability of concentration and yield measurements from test specimens in the steady-state tube furnace	27
14.4	Correlation of effluent yields from the steady-state tube furnace with those obtained from large-scale compartment fire tests under the same combustion conditions	27
15	Repeatability and reproducibility	28
Annex A (informative) Guidance on the choice of additional decomposition conditions		30
Annex B (informative) Estimation of lethal toxic potency for combustion products according to ISO 13344 using tube-furnace data		32
Annex C (informative) Application of data from the tube-furnace test to estimation and assessment of toxic hazard in fires according to ISO 13571		33
Annex D (informative) Use of the tube-furnace method for bioassay purposes		34
Annex E (informative) Measurement of optical density from the steady-state tube furnace		35
Annex F (informative) Comparison of data from the steady-state tube furnace, the ISO 9705 room and other compartment fire experiments		37
Annex G (informative) Assessment of mass-loss rate data		41
Bibliography		46