

DIN EN ISO 12569:2018-04 (E)

Thermal performance of buildings and materials - Determination of specific airflow rate in buildings - Tracer gas dilution method (ISO 12569:2017)

Contents	Page
European foreword	4
Foreword	5
Introduction	6
1 Scope	7
2 Normative references	7
3 Terms and definitions	7
4 Measurement method and its selection	8
4.1 General	8
4.2 Concentration decay method	10
4.2.1 Principle	10
4.2.2 Two-point decay method	11
4.2.3 Multipoint decay method	12
4.2.4 Step-down exhaust concentration method	12
4.2.5 Pulse method	13
4.3 Continuous dose method	14
4.3.1 Principle	14
4.3.2 Average inverse concentration method	14
4.3.3 Average concentration method	15
4.3.4 Stationary concentration method	16
4.4 Constant concentration method	16
4.5 Type of tracer gas	16
4.6 Measurement apparatus	17
4.6.1 General	17
4.6.2 Tracer gas dosing device	19
4.6.3 Tracer gas sampling apparatus	20
4.6.4 Gas analyser	20
5 Procedure	20
5.1 Building preparations	20
5.2 Ancillary measurements	20
5.3 Concentration decay method	21
5.3.1 Calculation of two-point and multi-point methods	21
5.3.2 Procedure of two-point and multi-point methods	22
5.3.3 Calculation of step-down exhaust concentration method and pulse method	23
5.3.4 Procedure of the step-down exhaust concentration method and pulse method	24
5.4 Continuous dose methods	27
5.4.1 Calculation of average of inverse concentration method	27
5.4.2 Procedure of average of inverse concentration method	28
5.4.3 Calculation of average concentration method	29
5.4.4 Procedure of average concentration method	30
5.4.5 Calculation of stationary concentration method	31
5.4.6 Procedure of stationary concentration method	31
5.5 Constant concentration method	33
5.5.1 Calculation of constant concentration method	33
5.5.2 Procedure of constant concentration method	33
6 Accuracy	34
6.1 General	34
6.2 Tracer gas dose procedure and room concentration distribution	35

6.3	Tracer gas sampling and storage method	35
6.4	Tracer gas concentration measuring instruments	35
6.4.1	General	35
6.4.2	Resolution	35
6.4.3	Tracer gas analyser drift	35
6.4.4	Accuracy of tracer gas analyser	35
6.4.5	Calibration of tracer gas analyser	36
6.4.6	Standard gas concentration	36
6.5	Changes in outside wind and outdoor air temperature and schedule of air conditioning system	36
7	Test report	36
7.1	General	36
7.2	Details necessary to identify the simulation tested	37
7.3	Details of heating and ventilation systems	37
7.4	Test conditions and apparatus	37
7.5	Collected data and results	37
7.6	Date of the test	38
Annex A (normative) Confidence intervals		39
Annex B (normative) Method to estimate ventilation rate Q_v and effective mixed zone volume V_{emz} simultaneously[3][4]		42
Annex C (informative) Considerations when measuring the ventilation rate of large spaces		47
Annex D (informative) Effects of internal and external temperature difference, temperature change, and outdoor air concentration change during the measurement period		48
Annex E (informative) Estimation error minimizing method in two-point and multi-point decay methods		52
Annex F (informative) Propagation of error analysis		57
Bibliography		59