ISO 20657:2017-03 (E)

Glass in building - Heat soaked tempered soda lime silicate safety glass

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Glass products 3

5 Manufacturing processes 3
5.1 General 3
5.2 Tempering process 3
5.3 Heat soak process cycles 4
5.3.1 Off-line process 4
5.3.2 In-line process 7

6 Fracture characteristics 8
6.1 General 8
6.2 Accidental human impact 8
6.3 Fragmentation 8

7 Dimensions and tolerances 9
7.1 Nominal thickness and thickness tolerances 9
7.2 Width and length (sizes) 9
7.2.1 General 9
7.2.2 Maximum and minimum sizes 10
7.2.3 Tolerances and squareness 10
7.2.4 Edge deformation produced by vertical tempering 11
7.3 Flatness 11
7.3.1 General 11
7.3.2 Measurement of overall bow 13
7.3.3 Measurement of wave or roller wave distortion 14
7.3.4 Measurement of edge lift (only for heat soaked tempered safety glass which was horizontally tempered) 15
7.3.5 Measurement of perimeter deformation of glass produced by air cushion tempering process 16
7.3.6 Measurement of local distortion (only for heat soaked tempered safety glass which was vertically tempered) 16
7.3.7 Limitation on overall bow, roller waves and edge lift for heat soaked tempered safety glass which was horizontally tempered 17
7.3.8 Limitation on overall bow, wave and perimeter deformation for heat soaked tempered safety glass manufactured by air cushion process 18
7.3.9 Limitation on overall bow and local distortion for heat soaked tempered safety glass which was vertically tempered 18
7.3.10 Other distortions 18

8 Edge work, holes, notches and cut-outs 19
8.1 General 19
8.2 Edge working of glass for tempering 19

8.3 Profiled edges 20
8.4 Round holes 20
8.4.1 General 20
8.4.2 Diameter of holes 20
8.4.3 Limitations on position of holes 20
8.4.4 Tolerances on hole diameters 21
8.4.5 Tolerances on position of holes 22
8.5 Holes/others 23
8.6 Notches and cut-outs 23
8.7 Shaped panes 23

9 Fragmentation test 23
9.1 General 23
9.2 Dimensions and number of test specimens 23
9.3 Test procedure 24
9.4 Assessment of fragmentation 24
9.5 Minimum values from the particle count 25
9.6 Selection of the longest particle 25
9.7 Maximum length of longest particle 25
9.8 Test Report 26

10 Other physical characteristics 26
10.1 Optical distortion 26
10.1.1 Heat soaked tempered safety glass produced by vertical tempering 26
10.1.2 Heat soaked tempered safety glass produced by horizontal tempering 26
10.2 Anisotropy (iridescence) 26
10.3 Thermal durability 26
10.4 Mechanical strength 27
10.5 Surface pre-stress 27

11 Marking 27

12 Packaging 28

Annex A (informative) Pendulum impact test methods 29

Annex B (informative) Alternative method for the measurement of roller wave distortion 30

Annex C (informative) Example of particle count 32

Annex D (informative) Method for the measurement of the surface pre-stress of heat soaked tempered safety glass 34

Annex E (informative) In-line heat soak process control 36

Annex F (informative) Heat soak process system calibration test 38

Bibliography 48