

ISO 21927-8:2017-04 (E)

Smoke and heat control systems - Part 8: Smoke control dampers

| Contents | | Page |
|--|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Smoke control damper requirements | 5 |
| 4.1 | General | 5 |
| 4.1.1 | Fire resistance | 5 |
| 4.1.2 | General application | 5 |
| 4.2 | Construction and components: Characteristics | 5 |
| 4.2.1 | Construction and operation | 5 |
| 4.2.2 | Protection against corrosion | 7 |
| 4.3 | Fire resistance performance criteria: Single-compartment smoke control dampers | 7 |
| 4.3.1 | Integrity, leakage, HOT400/30 | 7 |
| 4.3.2 | Durability | 7 |
| 4.3.3 | Fire resistance classification and designation | 8 |
| 4.3.4 | Other performance criteria | 8 |
| 4.4 | Fire resistance performance criteria: Multi-compartment fire-resisting smoke control dampers | 9 |
| 4.4.1 | Integrity, insulation, leakage, HOT400/30 | 9 |
| 4.4.2 | Durability | 9 |
| 4.4.3 | Fire resistance classification and designation | 10 |
| 4.4.4 | Other performance criteria | 10 |
| 5 | Test methods | 10 |
| 5.1 | Ambient leakage tests | 10 |
| 5.2 | Fire resistance tests | 10 |
| 5.2.1 | General | 10 |
| 5.2.2 | Smoke control damper: Integrity and insulation | 12 |
| 5.2.3 | Leakage rated smoke control damper | 12 |
| 5.2.4 | Response delay of a smoke control damper | 12 |
| 5.3 | Salt spray exposure test | 12 |
| 5.4 | Cycling tests | 12 |
| 5.5 | Damper aerodynamic performance | 12 |
| 6 | Marking and documentation | 13 |
| 7 | Product, installation and maintenance information (documentation) | 14 |
| 7.1 | Product specification | 14 |
| 7.2 | Installation information | 14 |
| 7.3 | Maintenance information | 14 |
| Annex A (normative) Salt spray exposure test | | 15 |
| Annex B (informative) Example of inspection and maintenance procedure | | 16 |
| Bibliography | | 17 |