

# DIN EN 12274-5:2018-05 (E)

## Slurry surfacing - Test method - Part 5: Determination of the minimum binder content and wearing resistance

---

<b>Contents</b>		<b>Page</b>
European foreword .....		3
1	Scope .....	4
2	Normative references .....	4
3	Terms and definitions .....	4
4	Principle .....	4
5	Materials .....	5
5.1	Coarse aggregates and fine aggregates .....	5
5.2	Reactive filler .....	5
5.3	Emulsion .....	5
6	Apparatus .....	5
6.1	Apparatus used for preparation of samples .....	5
6.2	Apparatus used for testing .....	6
7	Preparation of sample .....	9
7.1	Conditioning temperature .....	9
7.2	Water addition .....	10
7.3	Aggregates and reactive filler .....	10
7.4	Water and additive .....	10
7.5	Emulsion .....	10
7.6	Sample size .....	10
7.7	Curing .....	11
8	Test procedure .....	11
9	Expression of results .....	12
9.1	Test sample mass .....	12
9.2	Conversion factor .....	12
9.3	Test result .....	12
10	Test report .....	12
11	Precision .....	12
Annex A (informative) Minimum amount of emulsion for slurry surfacing with a given aggregate composition to withstand the abrasive action of traffic .....		13
Annex B (informative) Resistance to wear of the mix at early stage under different traffic and climatic conditions .....		14
B.1	General .....	14
B.2	Curing .....	14
B.3	Test procedure for determining the resistance to wear .....	14