DIN EN 12274-5:2018-05 (E)

Slurry surfacing - Test method - Part 5: Determination of the minimum binder content and wearing resistanc e

Contents

Page

European foreword 3

1 Scope 4

2 Normative references 4

3 Terms and definitions 4

4 Principle 4

5 Materials 5
5.1 Coarse aggregates and fine aggregates 5
5.2 Reactive filler 5
5.3 Emulsion 5

6 Apparatus 5
6.1 Apparatus used for preparation of samples 5
6.2 Apparatus used for testing 6

7 Preparation of sample 9
7.1 Conditioning temperature 9
7.2 Water addition 10
7.3 Aggregates and reactive filler 10
7.4 Water and additive 10
7.5 Emulsion 10
7.6 Sample size 10
7.7 Curing 11

8 Test procedure 11

9 Expression of results 12
9.1 Test sample mass 12
9.2 Conversion factor 12
9.3 Test result 12

10 Test report 12

11 Precision 12

Annex A (informative) Minimum amount of emulsion for slurry surfacing with a given aggregate composition to withstand the abrasive action of traffic 13

Annex B (informative) Resistance to wear of the mix at early stage under different traffic and climatic conditions 14

B.1 General 14
B.2 Curing 14
B.3 Test procedure for determining the resistance to wear 14