

ISO 8375:2017-06 (E)

Timber structures - Glued laminated timber - Test methods for determination of physical and mechanical properties

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Symbols and suffixes | 2 |
| 4.1 | Symbols | 2 |
| 4.2 | Suffixes | 3 |
| 5 | Determination of dimensions of test specimens | 3 |
| 6 | Determination of moisture content of test specimens | 3 |
| 7 | Determination of density of test specimens | 4 |
| 8 | Conditioning of test specimens | 4 |
| 9 | Determination of local (shear-free) modulus of elasticity of the beam in bending | 4 |
| 9.1 | Test specimen | 4 |
| 9.2 | Procedure | 4 |
| 9.3 | Expression of results | 5 |
| 10 | Determination of global modulus of elasticity of the beam in bending | 6 |
| 10.1 | Test specimen | 6 |
| 10.2 | Procedure | 6 |
| 10.3 | Expression of results | 7 |
| 11 | Determination of shear modulus of the beam -- Variable span method | 7 |
| 11.1 | General | 7 |
| 11.2 | Test piece | 8 |
| 11.3 | Procedure | 8 |
| 11.4 | Expression of results | 9 |
| 11.4.1 | Determination of K1 and K2 | 9 |
| 11.4.2 | Shear modulus | 9 |
| 12 | Determination of bending strength of the beam | 10 |
| 12.1 | Test specimen | 10 |
| 12.2 | Procedure | 10 |
| 12.3 | Expression of results | 11 |
| 13 | Determination of the modulus of elasticity in tension parallel to the grain of the glued laminated timber | 11 |
| 13.1 | General | 11 |
| 13.2 | Test specimen | 11 |
| 13.3 | Procedure | 11 |
| 13.4 | Expression of results | 12 |
| 14 | Determination of the parallel to the grain tension strength of the glued laminated timber | 12 |

| | | |
|--------|--|----|
| 14.1 | Test specimen | 12 |
| 14.2 | Procedure | 12 |
| 14.3 | Expression of results | 12 |
| 15 | Determination of the modulus of elasticity in compression parallel to the grain of the glued laminated timber | 13 |
| 15.1 | General | 13 |
| 15.2 | Test specimen | 13 |
| 15.3 | Procedure | 13 |
| 15.4 | Expression of results | 13 |
| 16 | Determination of the parallel to grain compression strength of the glued laminated timber | 14 |
| 16.1 | Test specimen | 14 |
| 16.2 | Procedure | 14 |
| 16.3 | Expression of results | 14 |
| 17 | Determination of the modulus of elasticity in compression and tension perpendicular to the grain of the glued laminated timber | 14 |
| 17.1 | Requirements for test specimens | 14 |
| 17.2 | Procedure | 15 |
| 17.3 | Expression of results | 15 |
| 17.3.1 | Compression perpendicular to the grain | 15 |
| 17.3.2 | Tension perpendicular to the grain | 16 |
| 18 | Determination of tension and compression strengths perpendicular to the grain of the glued laminated timber | 17 |
| 18.1 | Requirements for test specimens | 17 |
| 18.1.1 | Fabrication | 17 |
| 18.1.2 | Surface preparation | 17 |
| 18.2 | Procedure | 17 |
| 18.3 | Expression of results | 19 |
| 18.3.1 | Compression perpendicular to the grain | 19 |
| 18.3.2 | Tension perpendicular to the grain | 20 |
| 19 | Determination of shear strength parallel to the grain -- Small specimen test | 20 |
| 19.1 | Requirements for test specimens | 20 |
| 19.1.1 | Fabrication | 20 |
| 19.1.2 | Surface preparation | 20 |
| 19.2 | Procedure | 21 |
| 19.3 | Expression of results | 22 |
| 20 | Determination of shear strength parallel to the grain -- Full size beam test | 23 |
| 20.1 | Specimen | 23 |
| 20.2 | Procedure | 23 |
| 20.3 | Expression of result | 24 |
| 21 | Test report | 25 |
| 21.1 | General | 25 |
| 21.2 | Test specimen | 25 |
| 21.3 | Test method | 25 |
| 21.4 | Test results | 25 |
| | Bibliography | 26 |