

ISO/TR 24679-2:2017-07 (E)

Fire safety engineering - Performance of structure in fire - Part 2: Example of an airport terminal

| Contents | | Page |
|-----------------------|---|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms, definitions and symbols | 1 |
| 4 | Design strategy for fire safety of structures | 3 |
| 5 | Quantification of the performance of structures in fire | 3 |
| 5.1 | Step 1: Scope of the project for fire safety of structures | 3 |
| 5.1.1 | Built environment characteristics | 3 |
| 5.1.2 | Fuel loads | 4 |
| 5.1.3 | Mechanical actions | 5 |
| 5.2 | Step 2: Identify objectives, functional requirements and performance criteria for fire safety of structures | 6 |
| 5.3 | Step 3: Trial design plan for fire safety of structures | 7 |
| 5.4 | Step 4: Design fire scenarios and design fires | 9 |
| 5.4.1 | Design fire scenarios | 10 |
| 5.4.2 | Design fires (thermal actions) | 11 |
| 5.5 | Step 5: Thermal response of the structure | 17 |
| 5.5.1 | Smoke temperature from FDS simulation | 17 |
| 5.5.2 | Calculating steel temperature exposed to smoke | 19 |
| 5.6 | Step 6: Mechanical response of the structure | 20 |
| 5.6.1 | Deformation analysis of the structure | 21 |
| 5.6.2 | Strength analysis of the main span under fire exposure | 22 |
| 5.7 | Step 7: Assessment against the fire safety objectives | 26 |
| 5.8 | Step 8: Documentation of the design for fire safety of structures | 27 |
| 5.9 | Factors and influences to be considered in the quantification process | 28 |
| 5.9.1 | Material properties | 28 |
| 5.9.2 | Effect of continuity and restraint (interaction between elements and materials) | 30 |
| 5.9.3 | Use of test results | 30 |
| 5.9.4 | Fire spread routes | 30 |
| 6 | Guidance on use of engineering methods | 31 |
| Annex A (informative) | Views and plans of the airport terminal | 32 |
| Bibliography | | 34 |