

# DIN EN ISO 12570:2018-07 (E)

Hygrothermal performance of building materials and products - Determination of moisture content by drying at elevated temperature (ISO 12570:2000 + Amd 1:2013 + Amd 2:2018)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
European foreword to Amendment A1 .....		4
European foreword to Amendment A2 .....		5
Foreword to Amendment AMD 2 .....		6
Introduction .....		7
<b>1</b>	<b>Scope .....</b>	<b>8</b>
<b>2</b>	<b>Normative references .....</b>	<b>8</b>
<b>3</b>	<b>Definitions, symbols and units .....</b>	<b>8</b>
<b>3.1</b>	<b>Definitions .....</b>	<b>8</b>
<b>3.2</b>	<b>Symbols and units .....</b>	<b>8</b>
<b>4</b>	<b>Principle .....</b>	<b>9</b>
<b>5</b>	<b>Apparatus .....</b>	<b>9</b>
<b>6</b>	<b>Test specimens .....</b>	<b>9</b>
<b>6.1</b>	<b>Dimensions and number of test specimens .....</b>	<b>9</b>
<b>6.2</b>	<b>Preparation of test specimens .....</b>	<b>9</b>
<b>7</b>	<b>Procedure .....</b>	<b>10</b>
<b>7.1</b>	<b>Test conditions .....</b>	<b>10</b>
<b>7.2</b>	<b>Procedure for test specimens weighed immediately after cutting from sample .....</b>	<b>10</b>
<b>7.3</b>	<b>Procedure for test specimens, sealed vapour tight after cutting from sample .....</b>	<b>11</b>
<b>8</b>	<b>Calculation and expression of results .....</b>	<b>11</b>
<b>8.1</b>	<b>Moisture content mass by mass .....</b>	<b>11</b>
<b>8.1.1</b>	<b>Test specimens weighed immediately after cutting from sample .....</b>	<b>11</b>
<b>8.1.2</b>	<b>Test specimens sealed vapour tight after cutting from sample .....</b>	<b>12</b>
<b>8.2</b>	<b>Moisture content mass by volume .....</b>	<b>12</b>
<b>8.3</b>	<b>Moisture content volume by volume .....</b>	<b>12</b>
<b>8.4</b>	<b>Dry density .....</b>	<b>12</b>
<b>8.5</b>	<b>Test result .....</b>	<b>13</b>
<b>9</b>	<b>Accuracy of measurement .....</b>	<b>13</b>
<b>10</b>	<b>Test report .....</b>	<b>13</b>
<b>Annex A (informative)</b>	<b>Bibliography .....</b>	<b>14</b>