ISO 17892-12:2018 (E)

Geotechnical investigation and testing — Laboratory testing of soil — Part 12: Determination of liquid and plastic limits

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Apparatus

- 4.1 General
- 4.2 Fall cone method
- 4.3 Casagrande method
- 4.4 Plastic limit equipment

5 Test procedure

- 5.1 Choice of liquid limit method
- 5.2 Specimen preparation
- 5.3 Determination of liquid limit by the fall cone method
- 5.4 Determination of liquid limit by the Casagrande method
- 5.5 Determination of plastic limit

6 Test results

- 6.1 Proportion of sample smaller than 0,4 mm
- 6.2 Liquid limit by the fall cone method
- 6.3 Liquid limit by the Casagrande method
- 6.4 Plastic limit
- 6.5 Plasticity index

7 Test report

- 7.1 Mandatory reporting
- 7.2 Optional reporting

Annex A (normative) Calibration, maintenance and checks

- A.1 General requirements
- A.2 Environmental conditions
- A.3 Apparatus
- A.3.1 Ovens
- A.3.2 Thermometers
- A.3.3 Balances
- A.3.4 Separation sieves
- A.3.5 Timers
- A.3.6 Fall cone liquid limit device
- A.3.6.1 Cone
- A.3.6.2 Penetration measurement device
- A.3.7 Casagrande liquid limit device
- A.3.7.1 Dimensions
- A.3.7.2 Dimensions of the cam
- A.3.7.3 Grooving tools
- A.3.7.4 Daily checks
- A.3.7.5 Annual checks
- A.4 Plastic limit equipment

Annex B (normative) Additional parameters

B.1 Additional parameters
B.1.1 Liquidity index
B.1.2 Consistency index
B.1.3 Activity index
B.1.4 Water content of the specimen passing 0,4 mm or nearest sieve
B.2 Plasticity chart

Page count: 27