DIN EN 12697-31:2020-04 (E)

Bituminous mixtures - Test methods - Part 31: Specimen preparation by gyratory compactor

Contents

Page

European foreword 4

1 Scope 6

2 Normative references 6

3 Terms, definitions and symbols 6
3.1 Terms and definitions 6
3.2 Symbols 7

4 Principle 9

5 Apparatus 9
5.1 Test device 9
5.2 Metallic moulds 10
5.3 Round metallic inserts 10
5.4 Device for measuring the distance between inserts 10
5.5 Device for counting the number of rotations with a precision of one revolution 10
5.6 Other usual equipments 10

6 Preparation of specimens 11
6.1 Mass of mixture to be introduced in the mould 11
6.1.1 Preparation of specimens for further mechanical testing 11
6.1.2 Preparation of specimens for void content requirement 11
6.2 Preparation of mixtures 12

7 Test procedure 13
7.1 Preliminary setting 13
7.1.1 Pre-load stress 13
7.1.2 Stress 13
7.1.3 Setting of the angle of inclination 13
7.1.4 Speed of rotation 13
7.1.5 Temperature 13
7.2 Compaction 13
7.2.1 Start of compaction 13
7.2.2 Specimens for void content requirement 13
7.2.3 Specimens for further testing 14

8 Precision 14

9 Test report 15

Annex A(normative) Procedure for setting the stress for types of gyratory compactor for compactability test 16

A.1 General 16
A.2 Principle 16
A.3 Gyratory-type testing procedure 16
A.3.1 Force adjustment 16
A.3.2 Angle 16

Annex B(normati ve) Procedure to evaluate the gyratory compactor (GC) internal angle of gyration and related parameters using simulated loading 17

B.1 General 17
B.2 Principle 17
B.3 Procedure 17
B.3.1 Calibration procedure with internal load simulator device 17
B.3.2 Calibration procedure with dynamic angle validator device 17
B.4 Calculation of results 18
B.4.1 Calculation of results for calibration procedure with internal load simulator device 18
B.4.2 Calculation of results for calibration procedure with dynamic angle validator device 19
B.5 Compliance 20
B.6 Precision and bias 20
B.7 Report 21

Bibliography 23