DIN EN 1793-5:2018-12 (E)

Road traffic noise reducing devices - Te st method for determining the acoustic performance - Part 5: Intrinsic characteristics - In situ values of sound reflection under direct sound field conditions (includes Corrigendum :2018)

Contents

Page

European foreword 4

Introduction 6

1 Scope 8

2 Normative references 8

3 Terms and definitions 8

4 Symbols and abbreviations 13

5 Sound reflection index measurements 15
5.1 General principle 15
5.2 Measured quantity 15
5.3 Test arrangement 18
5.4 Measuring equipment 23
5.4.1 Components of the measuring system 23
5.4.2 Sound source 24
5.4.3 Test signal 24
5.5 Data processing 25
5.5.1 Calibration 25
5.5.2 Sample rate 26
5.5.3 Background noise 27
5.5.4 Signal subtraction technique 27
5.5.5 Adrienne temporal window 30
5.5.6 Placement of the Adrienne temporal window 32
5.5.7 Low frequency limit and sample size 33
5.6 Positioning of the measuring equipment 35
5.6.1 Maximum sampled area 35
5.6.2 Selection of the measurement positions 35
5.6.3 Reflecting objects 42
5.6.4 Safety considerations 42
5.7 Sample surface and meteorological conditions 42
5.7.1 Condition of the sample surface 42
5.7.2 Wind 42
5.7.3 Air temperature 42
5.8 Single-number rating of sound reflection DLRI 42
5.9 Measurement uncertainty 43
5.10 Measuring procedure 43
5.11 Test report 44

Annex A (informative) Measurement uncertainty 46

A.1 General 46
A.2 Measurement uncertainty based upon reproducibility data 46
A.3 Standard deviation of repeatability and reproducibility of the sound reflection index 46

Annex B (informative) Template of test report on sound reflection of road noise barriers 48

B.1 Overview 48
B.2 Test setup (example) 50
B.3 Test object and test situation (example) 51
B.4 Test Results (example) 53
B.4.1 Part 1 - Results in tabular form 53

DIN EN 1793-5:2018-12 EN 1793-5:2016 (E) B.4.2 Part 2 - Results in graphic form 54
B.5 Uncertainty (example) 54

Annex C (informative) Near field to far field relationship 56

Bibliography 57