ISO 19916-1:2018 (E)

Glass in building — Vacuum insulating glass — Part 1: Basic specification of products and evaluation methods for thermal and sound insulating performance

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Description of components

4.1 Glass types and characteristics
4.2 Pillars
4.3 Edge seal
4.4 Evacuation port
4.5 Getter

5 Optical and thermal properties

5.1 Optical properties
5.2 U-value (thermal transmittance)
5.2.1 Determination of the U-value
5.2.2 Test report
5.2.3 Calculation method for U-value of vacuum insulating glass with different glass thickness
5.3 Total solar energy transmittance (g-value)

6 Dimensional requirements

6.1 Thickness
6.1.1 Nominal thickness
6.1.2 Limit deviation on thickness
6.1.3 Measurement of thickness
6.2 Width B and length H
6.2.1 General
6.2.2 Limit deviations on width B and length H
6.2.3 Limit deviations on squareness
6.2.4 Displacement

7 Durability

7.1 Requirements
7.2 Test specimens
7.3 Test method

8 Measurement of sound insulation

Annex A (normative) Determination of steady-state U-value (thermal transmittance) — Heat flow meter method and guarded hot plate method

A.1 General
A.2 Basic formula
A.3 Test apparatus
A.3.1 Buffer plates
A.3.2 Heat flow meter method
A.3.3 Guarded hot plate method

A.4 Dimensions of specimen and metering area
A.4.1 Distance from edge seal
A.4.2 Dimensions of metering area
A.5 Measurements

Annex B (normative) Test method for durability

B.1 Durability test
B.1.1 General
B.1.2 Moisture and light resistance test
B.1.3 Thermal repeating test

Annex C (informative) Calculation method for thermal transmittance (U-value)

Annex D (informative) Contribution from the edges to the measurement of the thermal transmittance (U-value) of vacuum insulating glass

Annex E (informative) Maximum deviation in the measured thermal transmittance (U-value) of a vacuum insulating glass due to non-uniformities in the heat flow through the pillar array

Page count: 33