

ISO/TS 18178:2018 (E)

Glass in building — Laminated solar photovoltaic glass for use in buildings

Contents

| | |
|----------|---------------------------------|
| | Foreword |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Description of components |
| 4.1 | General |
| 4.2 | Types of glass |
| 4.3 | Typical types of solar cells |
| 4.4 | Interlayer |
| 4.5 | Interconnector |
| 4.6 | Insulating strip |
| 4.7 | Termination |
| 5 | Requirements |
| 5.1 | General |
| 5.2 | Appearance |
| 5.2.1 | Major visual defects |
| 5.2.2 | Defects in the main area |
| 5.2.3 | Defects in the edge area |
| 5.3 | Dimensions and edge finishing |
| 5.4 | High temperature test |
| 5.5 | Damp heat test |
| 5.6 | Radiation test |
| 5.7 | Thermal cycling test |
| 5.8 | Humidity freeze test |
| 5.9 | Measurement of NMOT |
| 5.10 | Hot-spot endurance test |
| 5.11 | Impact test |
| 5.12 | Ball drop test |
| 5.13 | Insulation test |
| 5.14 | Wet leakage current test |
| 5.15 | Robustness of terminations test |
| 6 | Test specimens |
| 7 | Test methods |
| 7.1 | Test sequences |
| 7.2 | Visual inspection |
| 7.3 | High temperature test |
| 7.4 | Damp heat test |
| 7.5 | Radiation test |
| 7.6 | Thermal cycling test |
| 7.7 | Humidity-freeze test |
| 7.8 | Measurement of NMOT |
| 7.9 | Hot-spot endurance test |
| 7.10 | Ball drop test |
| 7.10.1 | Purpose |
| 7.10.2 | Specimen |
| 7.10.3 | Apparatus |
| 7.10.3.1 | Impactor. |
| 7.10.3.2 | Impactor hold-release device. |

- 7.10.3.3 Specimen holder.
- 7.10.4 Procedure
- 7.11 Insulation test
- 7.12 Wet leakage current test
- 7.13 Robustness of terminations test

8 Designation

Page count: 13