

# DIN EN 12966:2019-02 (Englisch)

## Road vertical signs - Variable message traffic signs (includes Amendment :2018)

---

| <b>Contents</b>  |   | <b>Page</b> |
|--|---|-------------|
| European foreword .....  |   | 7           |
| Introduction .....   |   | 9           |
| <b>1</b>   | <b>Scope .....</b>  | <b>10</b>   |
| <b>2</b>   | <b>Normative references .....</b>   | <b>10</b>   |
| <b>3</b>   | <b>Terms and definitions .....</b>  | <b>11</b>   |
| <b>4</b>   | <b>Product characteristics .....</b>  | <b>15</b>   |
| <b>4.1</b>   | <b>Dimensions and tolerances requirements .....</b>                         | <b>15</b>   |
| <b>4.2</b>   | <b>General design requirement .....</b>                                     | <b>15</b>   |
| <b>4.3</b>   | <b>Visual performance requirements of continuous VMS .....</b>              | <b>15</b>   |
| <b>4.4</b>   | <b>Visual performance requirements of discontinuous VMS .....</b>           | <b>16</b>   |
| <b>4.5</b>   | <b>Physical performance requirements .....</b>                              | <b>25</b>   |
| <b>4.6</b>   | <b>Dangerous substances .....</b>   | <b>28</b>   |
| <b>5</b>   | <b>Testing, assessment and sampling methods .....</b>                       | <b>29</b>   |
| <b>5.1</b>   | <b>Test sequence .....</b>  | <b>29</b>   |
| <b>5.2</b>   | <b>Durability .....</b>   | <b>29</b>   |
| <b>5.3</b>   | <b>Test modules .....</b>   | <b>29</b>   |
| <b>5.4</b>   | <b>Physical performance test methods .....</b>                              | <b>31</b>   |
| <b>5.5</b>   | <b>Visual performance test methods .....</b>                                | <b>37</b>   |
| <b>6</b>   | <b>Assessment and verification of constancy of performance (AVCP) .....</b> | <b>46</b>   |
| <b>6.1</b>   | <b>General .....</b>  | <b>46</b>   |
| <b>6.2</b>   | <b>Type testing .....</b>   | <b>46</b>   |
| <b>6.3</b>   | <b>Factory production control (FPC) .....</b>                               | <b>52</b>   |
| <b>7</b>   | <b>Classification and designation .....</b>                                 | <b>59</b>   |
| <b>7.1</b>   | <b>General .....</b>  | <b>59</b>   |
| <b>7.2</b>   | <b>Continuous retro-reflective VMS .....</b>                                | <b>59</b>   |
| <b>7.3</b>   | <b>Continuous, externally illuminated retro-reflective VMS .....</b>        | <b>59</b>   |
| <b>7.4</b>   | <b>Discontinuous VMS .....</b>  | <b>60</b>   |
| <b>8</b>   | <b>Marking, labelling and packaging .....</b>                               | <b>61</b>   |
| <b>9</b>   | <b>Product information .....</b>  | <b>61</b>   |
| <b>Annex A (normative) Equivalent area .....</b>                               |   | <b>63</b>   |
| <b>A.1</b>   | <b>General .....</b>  | <b>63</b>   |
| <b>A.2</b>   | <b>Calculation of the luminance .....</b>                                   | <b>63</b>   |
| <b>A.3</b>   | <b>Calculation of non-matrix equivalent areas .....</b>                     | <b>66</b>   |
| <b>A.3.1</b>   | <b>Equivalent area for a line of elements .....</b>                         | <b>66</b>   |
| <b>A.3.2</b>   | <b>Equivalent area for a symbol fully populated with elements .....</b>     | <b>67</b>   |
| <b>A.3.3</b>   | <b>Equivalent area for a symbol partially populated with elements .....</b> | <b>67</b>   |
| <b>Annex B (normative) VMS performance declaration codes for marking .....</b> |   | <b>69</b>   |
| <b>B.1</b>   | <b>General .....</b>  | <b>69</b>   |

|  |   |     |
|--|---|-----|
| B.2  | Code for continuous retro-reflective VMS .....                        | 69  |
| B.3  | Code for externally illuminated continuous retro-reflective VMS ..... | 69  |
| B.4  | Code for discontinuous VMS .....                                      | 70  |
| Annex L (informative) Terminology used in this European Standard .....   |   | 71  |
| Annex M (informative) Guidance on graphics for discontinuous light emitting signs .....  |   | 73  |
| M.1  | General .....   | 73  |
| M.2  | Apparent luminance of lines and letter strokes .....                  | 73  |
| DIN EN 12966:2019-02 EN 12966:2014+A1:2018 (E) M.2.1 General .....   |   | 73  |
| M.2.2  | Further technical explanation of Apparent luminance .....             | 74  |
| M.3  | VMS with colour inversion .....                                       | 75  |
| M.4  | VMS without colour inversion .....                                    | 81  |
| Annex N (informative) Guidance on dimensions , luminance, beam width, legibility and efficiency<br>for discontinuous VMS ..... |   | 83  |
| N.1  | General .....   | 83  |
| N.2  | Dimensions .....  | 83  |
| N.2.1  | General .....   | 83  |
| N.2.2  | Text .....  | 84  |
| N.2.3  | Circles .....   | 84  |
| N.2.4  | Triangles .....   | 85  |
| N.3  | Luminance and beam width classes .....                                | 85  |
| N.4  | Beam width and distances of legibility .....                          | 90  |
| N.4.1  | Group of VMS, centred above the road .....                            | 90  |
| N.4.2  | Group of VMS, not centred above the road .....                        | 91  |
| N.4.3  | Curved road sections .....  | 92  |
| N.4.4  | Limits of legibility due to vertical beam .....                       | 93  |
| N.4.5  | Calculation of recognition time .....                                 | 95  |
| N.4.5.1  | General .....   | 95  |
| N.4.5.2  | Distances .....   | 95  |
| N.4.5.3  | Example..... of calculation of the recognition time                   | 95  |
| N.4.5.3.1  | General .....   | 95  |
| N.4.5.3.2  | Using beam width class B2 .....                                       | 96  |
| N.4.5.3.3  | Using beam width class B4 .....                                       | 97  |
| N.4.5.3.4  | Using beam width class B6 .....                                       | 97  |
| N.4.5.4  | Conclusions..... after calculation of recognition time                | 98  |
| N.4.6  | Luminance and luminance ratio .....                                   | 98  |
| N.4.7  | Beam width .....  | 99  |
| N.5  | Energy efficiency .....   | 99  |
| Annex O (informative) Specific design issues .....   |   | 100 |
| O.1  | Finish .....  | 100 |
| O.2  | Front panels .....  | 100 |
| O.3  | Front screens .....   | 100 |
| O.4  | Appearance .....  | 100 |
| O.5  | Electrolytic compatibility .....                                      | 100 |
| O.6  | Protection against thermal overload .....                             | 100 |
| O.7  | Physical security against unauthorized access .....                   | 100 |
| O.8  | Interfaces between VMS, control, and higher order equipment .....     | 100 |
| O.9  | Diagnostic .....  | 101 |
| Annex P (informative) Guidance for design of VMS messages .....  |   | 102 |
| P.1  | Design of VMS messages .....  | 102 |
| P.2  | Specifying text dimensions .....                                      | 103 |
| Annex Q (informative) Technical documentation .....  |   | 106 |

|   |  |     |
|---|--|-----|
| Q.1   | Sign enclosure .....                                       | 106 |
| Q.2   | Electrical equipment .....                                 | 106 |
| Q.3   | Mounting devices (if applicable) .....                     | 106 |
| Q.4   | Retro-reflective and non retro-reflective components ..... | 106 |
| Annex R (informative) Example of recommended summary of class combinations .....  |  | 108 |
| DIN EN 12966:2019-02 EN 12966:2014+A1:2018 (E) Annex ZA (informative) Relationship of this European Standard with Regulation (EU) No.305/2011 ..... |  | 116 |
| ZA.1 Scope and relevant characteristics .....   |  | 116 |
| ZA.2 System of Assessment and Verification of Constancy of Performance (AVCP) .....   |  | 119 |
| ZA.3 Assignment of AVCP tasks .....   |  | 119 |
| ZA.4 The following clauses are not related to Regulation (EU) No 305/2011: .....  |  | 120 |
| Bibliography .....  |  | 121 |
| Figures Figure 1 -- Chromaticity areas for the colour classes C1 and C2 plotted in the CIE 1931 chromaticity diagram .....                          |  | 18  |
| Figure 2 -- Examples of passed and failed luminance distributions .....   |  | 23  |
| Figure 3 -- Examples of variable message traffic sign test modules in front view - a) and c) - and side view b) .....                               |  | 31  |
| Figure 4 -- Side elevation of the set-up for the measurement of luminance and luminance ratio .....   |  | 38  |
| Figure 5 -- Layout examples for a test module and the positioning of the measuring area (circle) of the luminance meter .....                       |  | 43  |
| Figure A.1 -- Merging of elements .....   |  | 63  |
| Figure A.2 -- Character with a regular orthogonal matrix of (5 × 8) elements .....  |  | 64  |
| Figure A.3 -- Open line .....   |  | 66  |
| Figure A.4 -- Closed line .....   |  | 66  |
| Figure A.5 -- Example of symbol with an area fully populated with elements .....  |  | 67  |
| Figure A.6 -- Example of symbol with an area partially populated with elements .....  |  | 68  |
| Figure B.1 -- Code of performance classes of continuous retro-reflective VMS .....  |  | 69  |
| Figure B.2 -- Code of performance classes of externally illuminated continuous retro- reflective VMS .....  |  | 70  |
| Figure B.3 -- Code of performance classes of discontinuous VMS .....  |  | 70  |
| Figure L.1 -- Parts of a VMS .....  |  | 71  |
| Figure L.2 -- Test configuration .....  |  | 72  |
| Figure M.1 -- A legend seen at short (left), longer (centre), and very long distance (right) .....  |  | 74  |
| Figure M.2 -- Example for calculation of dimensions of circular mandatory VMS .....   |  | 78  |
| Figure M.3 -- Example for calculation of dimensions of circular mandatory VMS .....   |  | 79  |

|   |     |
|---|-----|
| Figure M.4 -- Example for calculation of dimensions of a triangular warning VMS .....   | 80  |
| Figure M.5 -- Example of VMS using (64 × 64) elements with colour inversion .....   | 81  |
| Figure M.6 -- Example of VMS using (48 × 48) elements with colour inversion .....   | 81  |
| Figure M.7 -- Example of VMS using (32 × 32) elements with colour inversion .....   | 81  |
| Figure M.8 -- Example of VMS using (64 × 64) elements, no colour inversion .....  | 82  |
| Figure M.9 -- Example of VMS using (48 × 48) elements, no colour inversion .....  | 82  |
| Figure M.10 -- Example of VMS using (32 × 32) elements, no colour inversion .....   | 82  |
| Figure N.1 -- Relation between classes .....  | 86  |
| Figure N.2 -- Example of coverage by beam width class B1 .....  | 87  |
| Figure N.3 -- Example of coverage by beam width class B3 .....  | 88  |
| Figure N.4 -- Example of coverage by beam width class B6 .....  | 89  |
| Figure N.5 -- Legibility of group of VMS, centred on gantry above the road .....  | 90  |
| Figure N.6 -- Legibility of group of VMS, mounted on cantilever aside the road .....  | 91  |
| Figure N.7-- Legibility of group of VMS, mounted on cantilever aside the road .....   | 93  |
| Figure N.8-- Legibility of group of VMS, mounted on cantilever aside the road .....   | 94  |
| Figure P.1 -- Example of the design of the letter E in a regular orthogonal matrix .....  | 102 |
| Figure P.2 -- Equivalent text dimensions using uppercase characters .....   | 103 |
| DIN EN 12966:2019-02 EN 12966:2014+A1:2018 (E) Figure P.3 -- Equivalent text dimensions using<br>upper- and lower-case characters ..... | 104 |
| Figure P.4 -- Equivalent text dimensions of full matrix display using proportional character spacing<br>.....                           | 105 |
| Figure R.1-- Example of summary of the characteristics of products .....  | 109 |
| Figure R.2 -- Example 1 for visual performance class combination .....  | 111 |
| Figure R.3 -- Example 2 for visual performance class combination .....  | 112 |
| Figure R.4 -- Example 3 for visual performance class combination .....  | 114 |
| Figure R.5 -- Example 4 for visual performance class combination .....  | 115 |
| Tables Table 1 -- Class designation of the visual performance parameters of VMS .....   | 16  |
| Table 2 -- Corner points (CIE 1931 chromaticity co-ordinates x, y) of the chromaticity areas for the<br>colours of class C1 .....       | 17  |
| Table 3 -- Corner points (CIE 1931 chromaticity co-ordinates x, y) of the chromaticity areas for the<br>colours of class C2 .....       | 17  |
| Table 4 -- Le and La luminance limits for white on reference axis .....   | 19  |
| Table 5 -- Le and La luminance limits for yellow on reference axis .....  | 20  |

|   |    |
|---|----|
| Table 6 -- Le and La luminance limits for orange on reference axis .....  | 20 |
| Table 7 -- Le and La luminance limits for green on reference axis .....   | 20 |
| Table 8 -- Le and La luminance limits for red on reference axis .....   | 21 |
| Table 9 -- Le and La luminance limits for blue on reference axis .....  | 21 |
| Table 10 -- Minimum luminance ratio values (LR) for various colours and classes R1, R2 and R3, at test angles on the reference axis and off the reference axis .....                                  | 22 |
| Table 11 -- Beam width classes .....  | 24 |
| Table 12 -- Class designation .....   | 25 |
| Table 13 -- Temperature range classes .....   | 25 |
| Table 14 -- Ingress protection level classes .....  | 26 |
| Table 15 -- Effect of voltage interruption .....  | 28 |
| Table 16 -- Operating voltage range, power-up activation and temporary overvoltage tests .....  | 32 |
| Table 17 -- Frequency and voltage tests .....   | 32 |
| Table 18 -- Impact test .....   | 33 |
| Table 19 -- Vibration test .....  | 33 |
| Table 20 -- Corrosion test .....  | 34 |
| Table 21 -- Water ingress test - Severity .....   | 34 |
| Table 22 -- Dust ingress test - Severity .....  | 34 |
| Table 23 -- Temperature test .....  | 35 |
| Table 24 -- Test angles (in degrees, with respect to the reference axis), used for the measurement of luminance under external illumination and luminance ratio .....                                 | 39 |
| Table 25 -- Test angles (in degrees, with respect to the reference axis), used for the measurement of luminance without external illumination .....   | 39 |
| Table 26 -- Test angles (in degrees, with respect to the reference axis), used for the measurement of beam width, and for uniformity of luminous intensity and colour of monochromatic elements ..... | 40 |
| Table 27 -- Test angles (in degrees, with respect to the reference axis), used for the measurement of uniformity of luminous intensity and colour of elements formed by mixing colours .....          | 41 |
| Table 28 -- Characteristics of continuous VMS .....   | 47 |
| Table 29 -- Characteristics of discontinuous VMS .....  | 49 |
| Table 30 -- Identification label .....  | 52 |
| Table 31 -- Minimum frequency of testing continuous VMS for product testing and evaluation as part of FPC .....   | 55 |
| DIN EN 12966:2019-02 EN 12966:2014+A1:2018 (E) Table 32 -- Minimum frequency of testing discontinuous VMS for product testing and evaluation as part of FPC .....                                     | 56 |

|  |            |
|--|------------|
| <b>Table M.1 -- Parameters for mandatory signs using a red circle .....</b>  | <b>76</b>  |
| <b>Table M.2 -- Parameters for mandatory signs using a red triangle .....</b>  | <b>77</b>  |
| <b>Table N.1 -- Minimum dimensions of text (mm) .....</b>  | <b>84</b>  |
| <b>Table N.2 -- Minimum dimensions of circles (mm) .....</b>   | <b>85</b>  |
| <b>Table N.3 -- Minimum dimensions of triangles (mm) .....</b>   | <b>85</b>  |
| <b>Table N.4 -- Examples for applications of beam width classes .....</b>  | <b>86</b>  |
| <b>Table N.5 -- Examples for recognition time depending on character height, speed and vertical<br/>beam width .....</b> | <b>94</b>  |
| <b>Table N.6 -- Conversion from speed unit km/h to m/s .....</b>   | <b>95</b>  |
| <b>Table ZA.1 -- Relevant clauses for continuous VMS .....</b>   | <b>116</b> |
| <b>Table ZA.2 -- Relevant clauses for discontinuous VMS .....</b>  | <b>118</b> |
| <b>Table ZA.3 -- Assignment of AVCP tasks for VMS under system 1 .....</b>   | <b>120</b> |