

# ISO 21927-2:2018 (E)

## Smoke and heat control systems — Part 2: Specifications for natural smoke and heat exhaust ventilators

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
5	Requirements
5.1	Nominal activation conditions/sensitivity
5.1.1	Initiation device
5.1.1.1	General
5.1.1.2	Automatic initiation or release device
5.1.2	Opening mechanism
5.1.2.1	General
5.1.2.2	Integral gas containers
5.1.3	Inputs and outputs
5.2	Response delay (response time)
5.2.1	Reliability
5.2.2	Opening under (snow/wind) load
5.2.3	Low ambient temperature
5.2.4	Opening under heat
5.3	Operational reliability
5.4	Effectiveness of smoke/hot gas extraction (aerodynamic free area)
5.5	Performance parameters under fire conditions
5.5.1	Resistance to heat
5.5.2	Mechanical stability
5.5.3	Reaction to fire
5.6	Performance under environmental conditions
5.6.1	Opening under load
5.6.2	Low ambient temperature
5.6.3	Stability under wind load
5.6.4	Resistance to wind-induced vibration
5.6.5	Resistance to heat
5.7	Durability
5.7.1	Response delay (response time)
5.7.2	Operational reliability
5.7.3	Performance parameters under fire conditions
6	Testing, assessment and sampling methods
7	Marking, labelling and packaging
Annex A	(normative) Classification
A.1	Nominal activation condition/sensitivity
A.2	Response delay
A.3	Operational reliability
A.4	Effectiveness of smoke/hot gas extraction (aerodynamic free area)
A.5	Performance parameters under fire conditions

- A.6 Performance under environmental conditions
- A.7 Durability
- A.7.1 Response delay (response time)
- A.7.2 Operational reliability
- A.7.3 Performance parameters under fire conditions

**Annex B (normative) Effectiveness of smoke/hot gas extraction (aerodynamic free area)**

- B.1 Determination of the aerodynamic free area
- B.2 Simple assessment procedure
- B.2.1 General
- B.2.2 Roof mounted NSHEV
- B.2.3 Wall-mounted NSHEV
- B.3 Experimental procedure
- B.3.1 General
- B.3.2 Test apparatus
- B.3.3 Test specimen
- B.3.4 Test procedure
- B.3.4.1 Roof mounted NSHEV
- B.3.4.2 Wall-mounted NSHEV
- B.3.5 Evaluation of test results
- B.3.6 Calculation of the coefficient of discharge for a family of NSHEV
- B.3.6.1 Discharge coefficient without wind
- B.3.6.1.1 Basic considerations
- B.3.6.1.2 NSHEV with flap opening angles larger than 60°
- B.3.6.1.3 NSHEV with flap opening angles 60° and less
- B.3.6.2 Discharge coefficient with wind
- B.3.6.2.1 Hinged single flap NSHEV
- B.3.6.2.2 Hinged double flap NSHEV, louvre type NSHEV and other NSHEV
- B.4 Test to check the aerodynamic test installations
- B.4.1 General
- B.4.2 Reference test without side wind
- B.4.3 Reference tests with side wind
- B.4.4 Evaluation of test results

**Annex C (normative) Test method for operational reliability and response time**

- C.1 Objective of the test
- C.2 Test conditions
- C.3 Test apparatus
- C.4 Test specimen
- C.5 Test procedure

**Annex D (normative) Test method for opening under load**

- D.1 Objective of the test
- D.2 Test conditions
- D.3 Test apparatus
- D.4 Test specimen
- D.5 Test procedure

**Annex E (normative) Test method for low ambient temperature**

- E.1 Objective of the test
- E.2 Test apparatus
- E.3 Test specimen
- E.4 Test procedure

**Annex F (normative) Test method for stability under wind load**

- F.1 Objective of the test
- F.2 Test conditions
- F.3 Test apparatus
- F.4 Test specimen
- F.5 Test procedure
- F.5.1 Wind load
- F.5.2 Vibration

**Annex G (normative) Test method for resistance to heat**

- G.1 Objective of the test
- G.2 Test apparatus
  - G.2.1 Test furnace
  - G.2.2 Temperature measurement
  - G.2.3 NSHEV mount
    - G.2.3.1 Roof mounted NSHEV
    - G.2.3.2 Wall-mounted NSHEV
- G.3 Test specimen
  - G.3.1 General
  - G.3.2 NSHEV mounted to a glazed partition construction
  - G.3.3 Roof mounted NSHEV as part of a continuous rooflight
  - G.3.4 Wall-mounted NSHEV
  - G.3.5 Roof mounted NSHEV
- G.4 Test procedure

**Annex H (normative) Mounting and fixing conditions for the SBI or small flame tests**

- H.1 General
- H.2 Class E
  - H.2.1 General
  - H.2.2 Small flame test in accordance to ISO 11925-2
- H.3 Class A2 to class D
  - H.3.1 General
  - H.3.2 Single Burning Item (SBI) test
- H.4 Non-combustible test and determination of the heat combustion

**Annex I (normative) Handling changes affecting declared performances for NSHEV**

- I.1 General
- I.2 Effectiveness of smoke/hot gas extraction
- I.3 Reliability
- I.4 Opening under load
- I.5 Opening at low ambient temperatures
- I.6 Wind load
- I.7 Resistance to heat

**Annex J (informative) Installation and maintenance information**

- J.1 Installation information
- J.2 Maintenance information

Page count: 63