

# ISO 3008-1:2019 (E)

## Fire resistance tests — Door and shutter assemblies — Part 1: General requirements

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Test equipment
5	Test conditions
6	Test specimen
6.1	Size of specimen
6.2	Number of specimens
6.3	Design of specimen
6.4	Construction
6.5	Verification
7	Installation of test specimen
7.1	General
7.2	Supporting construction
7.3	Test construction
7.3.1	Associated and supporting construction
7.3.2	Associated construction
7.3.3	Supporting construction
7.3.4	Restraint on supporting construction
7.4	Gaps
8	Conditioning
8.1	Moisture content
8.2	Mechanical
9	Application of instrumentation
9.1	Temperature measurements
9.1.1	Furnace-temperature measuring instrument
9.1.2	Unexposed-face thermocouples
9.2	Maximum temperature
9.3	Temperature of door frame
9.4	Pressure measurements
9.5	Heat-flux measurement
9.5.1	General
9.5.2	Apparatus
9.5.3	Procedure
9.5.3.1	General positioning
9.5.3.2	Specific locations
9.5.4	Measurement
9.6	Deflection
10	Test procedure

- 11           **Performance criteria**
  - 11.1        **Integrity**
  - 11.2        **Insulation**
- 12           **Test report**
- 13           **Field of direct application of test results**
  - 13.1        **General**
  - 13.2        **Timber constructions**
  - 13.3        **Steel constructions**
  - 13.4        **Glazed constructions**
  - 13.5        **Fixings/hardware**
- Annex A (normative) Conditioning requirements for supporting constructions**
  - A.1        **General**
  - A.2        **Requirements**
- Annex B (informative) Estimation of radiant heat flux using measured surface temperature and the Stefan-Boltzmann law**
  - B.1        **Introduction**
  - B.2        **Application**
    - B.2.1       **General**
    - B.2.2       **Specimen temperature measurement**
    - B.2.3       **Specimen emissivity**
  - B.3        **Example calculation**

Page count: 52