

DIN EN 13384-1:2019-09 (E)

Chimneys - Thermal and fluid dynamic calculation methods - Part 1: Chimneys serving one heating combustion (includes Amendment A1:2019)

| Contents | | Page |
|-------------------------|--|-------------|
| European foreword | | 5 |
| 1 | Scope | 7 |
| 2 | Normative references | 7 |
| 3 | Terms and definitions | 7 |
| 4 | Symbols and abbreviations | 12 |
| 5 | Calculation method for non-balanced flue chimneys | 17 |
| 5.1 | General principles | 17 |
| 5.2 | Pressure requirements | 17 |
| 5.2.1 | Negative pressure chimneys | 17 |
| 5.2.2 | Positive pressure chimneys | 18 |
| 5.3 | Temperature requirement | 19 |
| 5.4 | Calculation procedure | 19 |
| 5.5 | Flue gas data characterising the !combustion" appliance | 20 |
| 5.5.1 | General | 20 |
| 5.5.2 | !Flue gas mass flow and combustion air mass flow | 20 |
| 5.5.3 | Flue gas temperature | 21 |
| 5.5.4 | Minimum draught for the !combustion" appliance (PW) for negative pressure chimney | 22 |
| 5.5.5 | Maximum draught for the !combustion" appliance (PWmax) for negative pressure chimney | 23 |
| 5.5.6 | Maximum differential pressure of the !combustion" appliance (PWO) for positive pressure chimney | 23 |
| 5.5.7 | Minimum differential pressure of the !combustion" appliance (PWomin) for positive pressure chimney | 23 |
| 5.6 | Characteristic data for the calculation | 23 |
| 5.6.1 | General | 23 |
| 5.6.2 | Mean value for roughness (r) | 23 |
| 5.6.3 | Thermal resistance (1/) | 23 |
| 5.7 | Basic values for the calculation | 24 |
| 5.7.1 | Air temperatures | 24 |
| 5.7.2 | External air pressure (pL) | 26 |
| 5.7.3 | Gas constant | 26 |
| 5.7.4 | Density of the external air (L) | 26 |
| 5.7.5 | Specific heat capacity of the flue gas (cp) | 27 |
| 5.7.6 | Condensing temperature (Tsp) | 27 |
| 5.7.7 | Correction factor for temperature instability (SH) | 27 |
| 5.7.8 | Flow safety coefficient (SE) | 27 |
| 5.8 | Determination of the temperatures | 27 |
| 5.8.1 | General | 27 |
| 5.8.2 | Calculation of the coefficient of cooling (K) | 28 |
| 5.8.3 | Coefficient of heat transmission (kb) | 28 |
| 5.9 | Determination of the density of the flue gas and the velocity of the flue gas | 31 |
| 5.9.1 | Density of the flue gas (m) | 31 |
| 5.9.2 | Velocity of the flue gas (wm) | 31 |
| 5.10 | Determination of the pressures | 31 |
| 5.10.1 | Pressure at the flue gas inlet into the chimney | 31 |
| 5.10.2 | Theoretical draught available due to chimney effect (PH) | 32 |

| | | |
|--------|--|----|
| 5.10.3 | Pressure resistance of the chimney (PR) | 33 |
| 5.10.4 | Wind velocity pressure (PL) | 34 |
| 5.11 | Minimum draught required at the flue gas inlet into the chimney and maximum allowed draught (PZe and PZemax) and maximum and minimum differential pressure at the flue gas inlet into the chimney (PZOe and PZOemin) | 35 |
| 5.11.1 | General | 35 |
| 5.11.2 | Minimum and maximum draught for the "combustion" appliance (PW and PWmax) and maximum and minimum differential pressure of the "combustion" appliance (PWO and PWOmin) | 36 |
| 5.11.3 | Effective pressure resistance of the connecting flue pipe (PFV) | 36 |
| 5.11.4 | Pressure resistance of the air supply (PB) | 37 |
| 5.12 | Calculation of the inner wall temperature at the chimney outlet (Tiob) | 38 |
| 6 | Secondary air for negative pressure chimneys | 40 |
| 6.1 | General | 40 |
| 6.2 | Calculation method | 40 |
| 6.3 | Basic values for the calculation of secondary air | 40 |
| 6.3.1 | General | 40 |
| 6.3.2 | Mixing calculations | 40 |
| 6.4 | Pressures | 41 |
| 6.4.1 | Pressure resistance for the air supply with secondary air (PBNL) | 41 |
| 6.4.2 | Draught required for the secondary air devices (PNL) | 43 |
| 6.4.3 | Pressure resistance for that part of the connecting flue pipe before the secondary air device (PFV1) | 44 |
| 6.4.4 | Pressure requirement with secondary air | 44 |
| 6.5 | Temperature requirement with secondary air | 44 |
| 7 | Calculation method for balanced flue chimneys | 45 |
| 7.1 | General principles | 45 |
| 7.2 | Pressure requirements | 46 |
| 7.3 | Temperature requirements | 46 |
| 7.4 | Calculation procedure | 46 |
| 7.5 | Flue gas data characterizing the "combustion" appliance | 47 |
| 7.6 | Characteristic data for the calculation | 47 |
| 7.7 | Basic values for the calculation | 47 |
| 7.7.1 | Air temperatures | 47 |
| 7.7.2 | Other basic values | 48 |
| 7.8 | Determination of the temperatures | 48 |
| 7.8.1 | Non-concentric (separate) ducts | 48 |
| 7.8.2 | Concentric ducts - calculation based on a correction factor for heat radiation | 49 |
| 7.8.3 | Concentric ducts - calculation based on calculated heat radiation | 64 |
| 7.8.4 | Mean temperatures for pressure calculation | 68 |
| 7.9 | Determination of densities and velocities | 69 |
| 7.9.1 | Density and velocity of the flue gas | 69 |
| 7.9.2 | Density and velocity of the "combustion" air | 69 |
| 7.10 | Determination of pressures | 70 |
| 7.10.1 | Pressure at the flue gas inlet into the chimney | 70 |
| 7.10.2 | Theoretical draught due to chimney effect in the chimney segment (PH) | 70 |
| 7.10.3 | Pressure resistance in the chimney segment (PR) | 70 |
| 7.10.4 | Wind velocity pressure (PL) | 70 |
| 7.11 | Minimum draught required at the flue gas inlet into the chimney and maximum allowed draught (PZe and PZemax) and maximum and minimum differential pressure at the flue gas inlet into the chimney (PZOe and PZOemin) | 71 |
| 7.11.1 | General | 71 |
| 7.11.2 | Minimum and maximum draught for the "combustion" appliance (PW and PWmax) and maximum and minimum differential pressure of the "combustion" appliance (PWO and PWOmin) | 71 |
| 7.11.3 | Effective pressure resistance of the connection pipe (PFV) | 71 |
| 7.11.4 | Pressure resistance of the air supply | 71 |
| 7.12 | Calculation of the inner wall temperature at the chimney outlet (Tiob) | 74 |
| 8 | Consideration of the condensation heat of the flue gas water vapour | 75 |

| | | |
|--|---|-----|
| 8.1 | General | 75 |
| 8.2 | Onset of condensation | 75 |
| 8.3 | Calculation of the flue gas temperature at the outlet of a chimney segment with condensation (j NsegK) | 78 |
| 9 | Consideration of chimney fans | 83 |
| 9.1 | General | 83 |
| 9.2 | Inline fans | 84 |
| 9.3 | Exhaust fans | 85 |
| Annex A (informative) Calculation of thermal resistance | | 86 |
| Annex B (informative) Tables | | 87 |
| Annex C (informative) Chimney outlet with regard to adjacent buildings | | 104 |
| Annex D (informative) Determination of the gas constant R considering the condensation | | 105 |