

DIN EN 12697-46:2020-05 (E)

Bitumi nous mixtures - Test methods - Part 46: Low temperature cracking and properties by uniaxial tension tests

Contents		Page
European foreword		4
1	Scope	6
2	Normative references	6
3	Terms and definitions	6
4	Principle	8
5	Apparatus	9
5.1	Testing device for conducting UTST, TSRST, RT and TCT	9
5.1.1	General	9
5.1.2	Load device	9
5.1.3	Deformation measurement system	11
5.1.4	Load measurement system	11
5.1.5	Recording equipment	11
5.1.6	Thermostatic chamber	12
5.2	Testing device for conducting UCTST	12
5.2.1	Dynamic testing device	12
5.2.2	Monitoring system	12
5.2.3	Electronic signal amplifier	13
5.2.4	Thermostatic chamber	13
5.2.5	Recording equipment	13
6	Calibration	13
6.1	Testing device for conducting UTST, TSRST, relaxation test and tensile creep test	13
6.2	Testing device for conducting UCTST	13
7	Specimen preparation	14
7.1	Number of samples	14
7.2	Dimensions	14
7.3	Preparation	14
7.4	Bulk density	14
7.5	Drying	15
7.6	Storage	15
7.7	Mounting	15
7.8	Installation and conditioning	16
8	Procedure	16
8.1	Uniaxial tension stress test (UTST)	16
8.2	Thermal stress restrained specimen test (TSRST)	17
8.3	Relaxation test (RT)	17
8.4	Tensile creep test (TCT)	17
8.5	Uniaxial cyclic tensile stress test (UCTST)	18
8.5.1	Test temperature and test frequency	18
8.5.2	Base stress	18
8.5.3	Peak stress	18
9	Evaluation	19
9.1	Tension strength reserve	19

9.2	Uniaxial cyclic tensile stress test (UCTST)	21
10	Test report	22
10.1	General	22
10.2	General information	22
10.3	Information on specimen	22
10.4	Information on test method	22
10.5	Information on the test and results	22
10.5.1	Uniaxial tension stress test (UTST)	22
10.5.2	Thermal stress restrained specimen test (TSRST)	23
10.5.3	Tension strength reserve	23
10.5.4	Relaxation test (RT)	23
10.5.5	Tensile creep test (TCT)	23
10.5.6	Uniaxial cyclic tensile stress test (UCTST)	23
11	Precision	24
	Bibliography	25