

DIN 18008-2:2020-05 (E)

Glass in Building - Design and construction rules - Part 2: Linearly supported glazings

Contents

	Page
Foreword	3
1 Scope	4
2 Normative references	4
3 Terms and definitions.....	4
4 Construction products	4
5 Conditions for use	5
6 Actions and verifications	5
6.1 Verification of the ultimate limit state and serviceability limit state	5
6.2 Verification of residual load-bearing capacity	7
Annex A (informative) Approximation methods for determination of climatic loads and distribution of actions	8
A.1 General	8
A.2 Calculation of the individual panes' proportions δ_a and δ_i in the total bending stiffness	8
A.3 Calculation of the characteristic edge length a^*	9
A.4 Calculation of factor φ	9
A.5 Determination of the isochoric pressure p_0	10
A.6 Distribution of actions.....	10
Annex B (normative) Structures with verified residual load-bearing capacity	13
B.1 Overhead glazing.....	13
B.1.1 General	13
B.1.2 Glazing made of laminated safety glass (LSG).....	13
B.1.3 Glazing made of wired glass.....	13
B.2 Vertical glazing.....	13
Annex C (informative) Measures for ensuring the required reliability for the use of monolithic heat-soaked thermally toughened soda lime silicate safety glass in accordance with DIN EN 14179-1 and -2 above 4 m installation height.....	15
Bibliography	16

Figures

Figure A.1 — Examples: wind pressure (left), positive or negative pressure (centre or right)	10
--	----

Tables

Table A.1 — Factor B_V	9
Table A.2 — Distribution of actions	10
Table A.3 — Proportion of the stiffness of individual panes in the total stiffness.....	11