

# DIN EN 1993-1-8/NA:2020-11 (E)

## National Annex - Nationally determined parameters - Eurocode 3: Design of steel structures - Part 1-8: Design of joints

---

<b>Contents</b>	<b>Page</b>
Foreword .....	4
NA.1 Scope .....	5
NA.2.1 General .....	5
NA.2.2 National provisions .....	6
NCI re 1.2 Normative references .....	6
NDP re 1.2.6 (Reference standard group 6: Rivets) Note .....	6
NDP re 2.2(2) Note .....	6
NCI re 3.1.1 Galvanized bolts .....	6
NDP re 3.1.1(3) Note .....	7
NDP re 3.4.2(1) Note .....	7
NCI re 3.5 Bolted connections with components with internal threads and components with external threads .....	7
NCI re 3.13.1 Connections made with pins -- General .....	8
NCI re 4.5.2 Limit value for effective throat thicknesses .....	8
NCI re 4.5.3.2(6) .....	8
NDP re 5.2.1(2) Note .....	8
NCI re 6.2.7.1(13) and 6.2.7.1(14) Contact splices and compression force transfer .....	8
NDP re 6.2.7.2(9) Note .....	9
NCI Contact splices and compression force transfer .....	9
NCI Butt jointing of parts of cross section differing in thickness .....	10
NCI Welding of added flange plates at their ends .....	11
NCI Joints between flange plates .....	11
Annex NA.B(normative) Castings, forgings and components made of steels for quenching and tempering .....	14
NA.B.1 Materials .....	14
NA.B.2 Requirements .....	14
NA.B.3 Characteristic values .....	15

<b>NA.B.4 Welds .....</b>	<b>16</b>
<b>NA.B.5 Bolted connections .....</b>	<b>17</b>
<b>Bibliography .....</b>	<b>18</b>
<b>Figures Figure NA.1 -- Possible designs of contact splices (a) partial contact, b) and c) full contact) .....</b>	<b>9</b>
<b>Figure NA.2 -- Permissible tolerances, <math>1/500</math>, e 2 mm .....</b>	<b>9</b>
<b>Figure NA.3 -- Examples of bevelling of edges when butt jointing parts of cross section differing in thickness .....</b>	<b>11</b>
<b>Figure NA.4 -- Pre-connecting of flange plates .....</b>	<b>11</b>
<b>Figure NA.5 -- Preparation of a butt joint between superposed flange plates (examples) .....</b>	<b>12</b>
<b>Tables Table NA.1 -- Characteristic strength values of threaded stud materials .....</b>	<b>7</b>
<b>Table NA.B.1 -- Requirements regarding the internal and external condition of components made from cast steel and spheroidal graphite cast iron, subjected to predominately static loading .....</b>	<b>15</b>
<b>Table NA.B.2 -- Characteristic values for cast steel and iron .....</b>	<b>16</b>
<b>Table NA.B.3 -- Correlation factor <math>w</math> for fillet welds .....</b>	<b>17</b>