

DIN 4108-4:2020-11 (E)

Thermal insulation and energy economy in buildings - Part 4: Hygrothermal design values

| Contents | Page |
|---|------|
| Foreword | 4 |
| Introduction | 5 |
| 1 Scope | 6 |
| 2 Normative references | 6 |
| 3 Terms and definitions..... | 11 |
| 4 Hygrothermal characteristic values..... | 11 |
| 4.1 Building materials, building types and building components and elements..... | 11 |
| 4.2 Moisture content in equilibrium | 27 |
| 4.3 Conversion factors for the moisture content | 28 |
| 4.4 Thermal resistance of air layers..... | 29 |
| 4.5 Surface resistance | 29 |
| 4.6 Specific heat capacity | 29 |
| 4.7 Floors and ceilings | 29 |
| 5 Glazing, windows, doors and curtain walling..... | 31 |
| 5.1 Windows, window doors, external doors and roof windows..... | 31 |
| 5.1.1 Design values for windows, window doors,external doors and roof windows as in DIN EN 14351-1..... | 31 |
| 5.1.2 Air permeability as a function of design features of windows, window doors and external doors..... | 32 |
| 5.2 Insulating glass units as in DIN EN 1279-5..... | 33 |
| 5.2.1 Design values for the thermal transmittance..... | 33 |
| 5.2.2 Design values for the total solar energy transmittance (solar factor) and light transmittance | 33 |
| 5.3 Design values for curtain walling..... | 35 |
| 5.3.1 Design values for thermal transmittance..... | 35 |
| 5.3.2 Design value for total solar energy transmittance (solar factor) and light transmittance | 36 |
| 6 Rooflights..... | 36 |
| 6.1 Individual rooflights and continuous rooflights of plastic materials..... | 36 |
| 6.2 Glass constructions in roof areas (e.g. glass roofs) | 38 |
| 7 Design values for industrial, commercial and garage doors and gates | 39 |
| 8 Calculation of insulation thicknesses for pipelines | 39 |
| Annex A (normative) Determination of design values for masonry made from masonry units as in DIN EN 771..... | 43 |
| A.1 General | 43 |
| A.2 Extrapolation of the dry values of thermal conductivity $\lambda_{10,dry,unit}$ of units at the upper limit of the declared density and determination of $\lambda_{10,dry,unit,100\%}$ | 43 |
| A.3 Influence of moisture content and determination of $\lambda_{design,unit,100\%}$ | 45 |
| A.4 Consideration of the influence of joints and determination of $\lambda_{design,mas,100\%}$ | 45 |
| A.4.1 Numerical calculations..... | 45 |
| A.4.2 Simplified method for composite components as in DIN EN ISO 6946 | 45 |
| A.4.3 Tabular method | 45 |

| | | |
|------------------|---|-----------|
| A.5 | Classification of thermal conductivity $\lambda_{\text{design,mas,100\%}}$ and determination of the design value λ_{p} | 46 |
| | Bibliography | 47 |
| Tables | | |
| Table 1 | — Design values for thermal conductivity and guideline values for water vapour resistance factors | 12 |
| Table 2 | — Line 5 of Table 1 for thermal insulating materials in accordance with harmonized European Standards | 23 |
| Table 3 | — Moisture content in equilibrium of building materials | 27 |
| Table 4 | — Conversion factors for wall building materials | 28 |
| Table 5 | — Conversion factors for thermal insulation | 29 |
| Table 6 | — Thermal resistances of floors and ceilings | 29 |
| Table 7 | — Design value for the thermal transmittance of external doors $U_{\text{D,BW}}$ as a function of the design features | 32 |
| Table 8 | — Air permeability as a function of design features of windows, window doors and external doors | 32 |
| Table 9 | — Correction factors ΔU_{g} for calculating the design values $U_{\text{g,BW}}$ | 33 |
| Table 10 | — Total solar energy transmittance and light transmittance as a function of the design features, the U_{g} value and the thermal transmittance | 34 |
| Table 11 | — Correction factors c as a function of the emissivity ε_{n} | 35 |
| Table 12 | — Guideline values for light transmittance τ_{D65}, U_{t}- and g-values | 37 |
| Table 13 | — Design value $U_{\text{D,BW}}$ as a function of design features | 39 |
| Table 14 | — Determination of insulation thicknesses while maintaining the minimum requirement of the German Energy Savings Ordinance (EnEV) – 100 % requirement | 40 |
| Table 15 | — Determination of insulation thicknesses while maintaining the minimum requirement of the German Energy Savings Ordinance (EnEV) – 50 % requirement | 42 |
| Table A.1 | — Gradients of the thermal conductivity- density curve | 44 |
| Table A.2 | — Determination of $\lambda_{\text{design,mas,100\%}}$ for masonry with various joint materials | 46 |