

DIN EN 1366-4:2021-05 (E)

Fire resistance tests for service installations - Part 4: Linear joint seals

Contents		Page
European foreword		4
Introduction		6
1 Scope		7
2 Normative references		7
3 Terms and definitions		7
4 Test equipment		8
5 Test conditions		9
5.1 Heating conditions		9
5.2 Pressure conditions		9
6 Test specimen		9
6.1 General		9
6.2 Size		9
6.3 Number of test specimens		9
7 Installation of test specimen		10
7.1 General		10
7.2 Requirements for specific seal types		10
7.2.1 Seals made of fabrics		10
7.2.2 Seals made of foams (foamed in situ)		10
7.2.3 Membrane forming seals		11
7.2.4 Seals made of mineral wool (faced/coated or not faced/coated)		11
7.2.5 Linear joint seal made of mortar/plaster		12
7.2.6 Linear joint seal made of sealants		13
7.2.7 Linear joint seal made of pre-formed compressible strips		13
7.2.8 Linear joint seals made of pre-formed compressible composite strips		14
7.2.9 Linear joint seal made of pre-formed compressible ropes		15
7.2.10 Linear joint seal made of pre-formed strips		15
7.3 Supporting construction		16
7.3.1 General		16
7.3.2 Standard supporting construction		18
7.4 Test construction		21
7.5 Splice locations		24
7.6 Induced movement		24
8 Conditioning		24
9 Application of instrumentation		24
9.1 General		24
9.2 Thermocouples		24
9.2.1 Furnace thermocouples		24
9.2.2 Unexposed face thermocouples		24
9.3 Roving thermocouple		36
9.4 Deformation and deflection		36
9.5 Integrity measurement		37

10	Test procedure	37
10.1	General	37
10.2	Installation of test construction	37
10.3	Mechanically induced movement of the test specimen	37
10.4	Measurements and observations	37
11	Performance criteria	37
11.1	Insulation	37
11.2	Integrity	37
11.3	Expression of results	38
12	Test report	38
13	Field of direct application of test results	38
13.1	Orientation	38
13.2	Supporting construction	39
13.2.1	Rigid constructions	39
13.2.2	Flexible wall constructions	41
13.2.3	Flexible floor constructions	41
13.2.4	Non-standard supporting constructions	41
13.3	Seal position	41
13.4	Mechanically induced movement	41
13.5	Dimensions	42
13.5.1	Linear joint seal made of fabrics	42
13.5.2	Linear joint seal made of foams - foamed in situ	42
13.5.3	Membrane forming seals	42
13.5.4	Linear joint seal made of mineral wool (faced/coated or not faced/coated)	42
13.5.5	Linear joint seal made of mortar/plaster	42
13.5.6	Linear joint seal made of sealants	42
13.5.7	Linear joint seal made of pre-formed compressible strips	43
13.5.8	Linear joint seals made of pre-formed compressible composite strips	44
13.5.9	Linear joint seal made of pre-formed compressible ropes	44
13.5.10	Linear joint seal made of pre-formed strips	45
Annex A(normative)	Standard condition for linear joint seals with no mechanically induced movement of the joint faces	46
Annex B(normative)	Standard condition for linear joint seals with mechanically induced movement of the joint faces	47
Annex C(informative)	Guidance on the use of this document	52
Bibliography	56