

# DIN 18541-2:2021-01 (E)

## Thermoplastic waterstops for sealing joints in concrete - Part 2: Material requirements and testing

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>5</b>
<b>4</b>	<b>Requirements .....</b>	<b>5</b>
<b>5</b>	<b>Testing .....</b>	<b>6</b>
<b>5.1</b>	<b>Sampling and sample preparation .....</b>	<b>6</b>
<b>5.2</b>	<b>Surface condition .....</b>	<b>6</b>
<b>5.3</b>	<b>Dimensions .....</b>	<b>6</b>
<b>5.4</b>	<b>Shore A hardness .....</b>	<b>6</b>
<b>5.5</b>	<b>Tensile strength and strain at break .....</b>	<b>7</b>
<b>5.6</b>	<b>Tear strength .....</b>	<b>7</b>
<b>5.7</b>	<b>Behaviour at sub-zero temperatures .....</b>	<b>7</b>
<b>5.8</b>	<b>Behaviour after conditioning in saturated milk of lime .....</b>	<b>7</b>
<b>5.9</b>	<b>Behaviour after thermal ageing .....</b>	<b>7</b>
<b>5.10</b>	<b>Behaviour on exposure to microorganisms .....</b>	<b>7</b>
<b>5.11</b>	<b>Behaviour after weathering .....</b>	<b>7</b>
<b>5.12</b>	<b>Shear resistance of joint .....</b>	<b>7</b>
<b>5.13</b>	<b>Fire behaviour .....</b>	<b>8</b>
<b>5.14</b>	<b>Behaviour after conditioning in bitumen .....</b>	<b>8</b>
<b>6</b>	<b>Marking .....</b>	<b>8</b>
<b>Bibliography .....</b>		<b>9</b>
<b>Tables Table 1 -- Requirements .....</b>		<b>5</b>