

# DIN EN 1998-1/NA:2021-07 (E)

## National Annex - Nationally determined parameters - Eurocode 8: Design of structures for earthquake resistance - Part 1: General rules, seismic actions and rules for buildings, with CD-ROM

---

### Contents

Page

Foreword .....	7
NA.1 Scope .....	9
NA.2 National provisions .....	9
NA.2.1 General .....	9
NA.2.2 National provisions .....	12
NCI re 1.1.2(2) Scope of EN 1998-1.....	12
NDP re 1.1.2(7) Scope of EN 1998-1.....	12
NCI re 1.2 Normative references.....	13
NDP re 2.1(1)P Fundamental requirements .....	13
NCI re 2.1(4) Fundamental requirements .....	13
NDP re 3.1.1(4) General.....	13
NDP re 3.1.2(1) Identification of ground types .....	13
NDP re 3.2.1(1), (2) and (3) Seismic zones.....	15
NDP re 3.2.1(4) Seismic zones.....	16
NDP re 3.2.1(5)P Seismic zones.....	17
NDP re 3.2.2.1(4), 3.2.2.2(2)P Basic representation of the seismic action.....	17
NDP re 3.2.2.3(1)P Vertical elastic response spectrum.....	18
NCI re 3.2.2.4 Design ground displacement.....	19
NCI re 3.2.2.5(3)P Design spectrum for linear analysis.....	19
NDP re 3.2.2.5(4)P Design spectrum for linear analysis.....	19
NDP re 4.2.3.2(8) Criteria for regularity in plan.....	19
NDP re 4.2.4(2)P Combination coefficients for variable actions.....	19
NDP re 4.2.5(5)P Importance classes and importance factors.....	20
NCI re 4.2.5(5)P Importance classes and importance factors .....	20
NDP re 4.3.3.1(4) Methods of analysis .....	20
NDP re 4.3.3.1(8) Methods of analysis .....	21
NCI re 4.3.3.2.2(3) Base shear force.....	21
NCI re 4.3.3.2.4 Torsional effects .....	21
NCI re 4.3.3.4.2.1(1) Non-linear static (pushover) analysis.....	21
NCI re 4.3.3.4.2.1(2) and (3) Non-linear static (pushover) analysis.....	21
NCI re 4.3.3.4.2.3 Capacity curve.....	22
NCI re 4.3.3.4.2.3(2) Capacity curve.....	22
NCI re 4.3.3.4.2.6 Target displacement .....	22
NCI re 4.3.3.4.2.7 Procedure for the estimation of the torsional effects .....	22
NCI re 4.3.5.1 Non-structural elements.....	22
NCI re 4.4.2.1(1) Ultimate limit state.....	22
NDP re 4.4.2.5(2) Resistance of horizontal diaphragms .....	22
NDP re 4.4.3.2(2) Limitation of interstorey drift.....	23
NDP re 5.2.1(5) Energy dissipation capacity and ductility classes .....	23
NDP re 5.2.2.2(10) Behaviour factors for horizontal seismic actions.....	23
NDP re 5.2.4(1) and (3) Safety verifications .....	23
NCI re 5.3.2 Materials .....	23
NCI re 5.4.3.4.2(5) Detailing for local ductility.....	23
NCI re 5.4.3.4.2(6) Detailing for local ductility.....	23
NDP re 5.4.3.5.2(1) Shear resistance .....	23

NCI re 5.7(1) Design and detailing of secondary seismic elements .....	23
NDP re 5.8.2(3) Tie-beams and foundation beams .....	23
NDP re 5.8.2(4) Tie-beams and foundation beams .....	24
NDP re 5.8.2(5) Tie-beams and foundation beams .....	24
NDP re 5.11.1.3.2(3) Energy dissipation .....	24
NDP re 5.11.1.4 Behaviour factors.....	24
NDP re 5.11.1.5(2) Analysis of a transient situation .....	24
NDP re 5.11.3.4(7) Precast large-panel walls .....	24
NDP re 6.1.2(1)P Design concepts .....	24
NDP re 6.1.3(1) Safety verifications.....	24
NDP re 6.2(3) Materials .....	24
NDP re 6.2(7) Materials .....	25
NCI re 6.3.2 Behaviour factors .....	25
NDP re 6.5.5(7) Design rules for connections in dissipative zones .....	25
NDP re 6.7.4(2) Beams and columns.....	25
NDP re 7.1.2(1)P Design concepts .....	25
NDP re 7.1.3(1) and (3) Safety verifications.....	25
NDP re 7.1.3(4) Safety verifications.....	25
NDP re 7.7.2(4) Calculation .....	25
NCI re 8.2(4) Materials and properties of dissipative zones.....	25
NDP re 8.3(1) Ductility classes and behaviour factors .....	26
NCI re 8.4(1)P Structural analysis .....	26
NCI re 8.5.2 Detailing rules for connections.....	27
NCI re 8.6(4)P Safety verifications .....	27
NDP re 9.2.1(1) Types of masonry units.....	27
NDP re 9.2.2(1) Minimum strength of masonry units .....	27
NDP re 9.2.3(1) Mortar.....	27
NDP re 9.2.4(1) Masonry bond .....	27
NDP re 9.3(2) Types of construction and behaviour factors.....	27
NDP re 9.3(3) Types of construction and behaviour factors.....	27
NDP re 9.3(4) Types of construction and behaviour factors.....	27
NCI re 9.4(6) Structural analysis.....	28
NDP re 9.5.1(5) Design criteria and construction rules .....	29
NCI re 9.6(2)P Safety verifications .....	29
NDP re 9.6(3) Safety verifications .....	29
NDP re 9.7.2(1) Rules for “simple masonry buildings”.....	30
NCI re 9.7.2(1) Rules for “simple masonry buildings” .....	30
NCI re 9.7.2(2)b) Rules for “simple masonry buildings” .....	30
NCI re 9.7.2(2)c) Rules for “simple masonry buildings” .....	30
NCI re 9.7.2(3)b), c) Rules for “simple masonry buildings” .....	30
NCI re 9.7.2(3)d) Rules for “simple masonry buildings” .....	30
NCI re 9.7.2(3)e) Rules for “simple masonry buildings” .....	30
NDP re 9.7.2(5) Rules for “simple masonry buildings”.....	30
NDP re 10.3(2)P Fundamental requirements.....	30
<b>Annex NA.D (normative) Simplified design rules for simple structures of ordinary construction.....</b>	<b>31</b>
<b>NA.D.1 General.....</b>	<b>31</b>
<b>NA.D.2 Base shear force.....</b>	<b>31</b>
<b>NA.D.3 Distribution of the horizontal seismic forces.....</b>	<b>32</b>
<b>NA.D.4 Torsional effects .....</b>	<b>33</b>
<b>NA.D.5 Combination of the effects of the components of the seismic action .....</b>	<b>34</b>
<b>NA.D.6 Analysis of deformations .....</b>	<b>34</b>
<b>NA.D.7 Non-structural elements.....</b>	<b>35</b>
<b>NA.D.8 Stability analysis.....</b>	<b>37</b>
<b>NA.D.9 Foundations .....</b>	<b>38</b>
<b>NA.D.10 Special rules for masonry structures.....</b>	<b>39</b>

<b>Annex NA.E (informative) Seismic hazard maps and parameter values for describing the elastic horizontal response spectrum for <math>T_{NCR} = 975</math> years and <math>T_{NCR} = 2\,475</math> years</b> .....	40
<b>NA.E.1 Hazard maps for <math>T_{NCR} = 975</math> years and <math>T_{NCR} = 2\,475</math> years</b> .....	40
<b>NA.E.2 Parameter values for describing the elastic horizontal response spectrum for <math>T_{NCR} = 975</math> years and <math>T_{NCR} = 2\,475</math> years</b> .....	40
<b>Annex NA.F (informative) Explanation of the procedure for determining the seismic action in the case of shear wave velocities below 150 m/s</b> .....	43
<b>NA.F.1 Determination of response spectra for ground level</b> .....	43
<b>NA.F.2 Procedure for determining soil dynamic characteristics</b> .....	43
<b>Annex NA.G (informative) Schematic representation of the deep geology classes</b> .....	45
<b>Annex NA.H (normative) NDP and NCI re 9.7.2(1) Rules for “simple masonry buildings”</b> .....	47
<b>NA.H.1 NDP re 9.7.2(1) Rules for “simple masonry buildings”</b> .....	47
<b>NA.H.2 NCI re 9.7.2(1) Rules for “simple masonry buildings”</b> .....	47
<b>Annex NA.I (normative) Digital representation of the spectral accelerations for the hazard map according to Figure NA.1</b> .....	64
<b>Annex NA.J (informative) Digital representation of further spectral accelerations</b> .....	65
<b>Bibliography</b> .....	66

## Figures

<b>Figure NA.1 — Representation of the spatial distribution of the spectral response acceleration for the deep geology ratio A-R in the plateau region <math>S_{aP,R}</math> for a return period <math>T_{NCR} = 475</math> years</b> .....	16
<b>Figure NA.2 — Shape and description of the elastic acceleration response spectrum</b> .....	18
<b>Figure NA.3 — Wall height <math>h</math> and distance <math>h_0</math></b> .....	29
<b>Figure NA.D.1 — Eccentricities to be assumed for a seismic force acting in the y-direction</b> .....	34
<b>Figure NA.E.1 — Schematic representation of the spatial distribution of the spectral response acceleration for the deep geology ratio A-R in the plateau region <math>S_{aP,R}</math> for a return period <math>T_{NCR} = 975</math> years in the Federal Republic of Germany</b> .....	41
<b>Figure NA.E.2 — Schematic representation of the spatial distribution of the spectral response acceleration for the deep geology ratio A-R in the plateau region <math>S_{aP,R}</math> for a return period <math>T_{NCR} = 2\,475</math> years in the Federal Republic of Germany</b> .....	42
<b>Figure NA.G.1 — Schematic representation of the deep geology classes in the region of the contour line of <math>S_{aP,R} = 0,6\text{ m/s}^2</math></b> .....	46
<b>Figure NA.H.1 — Reduction factor <math>k_v</math> as a function of the relative bearing depth <math>a/t</math></b> .....	48

## Tables

Table NA.1 — Control periods for describing the horizontal elastic response spectrum ( $T_{NCR} = 475$ years) .....	17
Table NA.2 — Soil factor $S$ for describing the horizontal elastic response spectrum .....	18
Table NA.3 — Parameters for describing the vertical elastic response spectrum .....	19
Table NA.4 — Coefficients for $\varphi$ for calculating $\psi_{Ei}$ .....	20
Table NA.5 — Importance classes and importance factors .....	20
Table NA.6 — Design concept, structural types and upper limit values of the behaviour factors for the three ductility classes .....	26
Table NA.7 — Types of construction and upper limit of the behaviour factor .....	28
Table NA.8 — Minimum requirements for stiffening walls (shear walls) .....	29
Table NA.9 — Partial safety factors for masonry structures in the seismic design situation .....	30
Table NA.D.1 — Minimum wall thicknesses for non-load-bearing partitions .....	36
Table NA.D.2 — Maximum number of full storeys for buildings requiring a stability analysis by comparison with wind .....	38
Table NA.E.1 — Parameter values for describing the elastic horizontal response spectrum for the return periods $T_{NCR} = 975$ years and $T_{NCR} = 2\,475$ years .....	40
Table NA.H.1 — Minimum requirements for the cross-sectional area of shear walls relative to the floor plan area as a percentage, with significant floor restraint for spectral accelerations $\leq 1,25$ m/s <sup>2</sup> and 1,70 m/s <sup>2</sup> .....	50
Table NA.H.2 — Minimum requirements for the cross-sectional area of shear walls relative to the floor plan area as a percentage, with significant floor restraint for spectral accelerations of 2,10 m/s <sup>2</sup> and 2,60 m/s <sup>2</sup> .....	51
Table NA.H.3 — Minimum requirements for the cross-sectional area of shear walls relative to the floor plan area as a percentage, with significant floor restraint for spectral accelerations of 3,00 m/s <sup>2</sup> and 3,60 m/s <sup>2</sup> .....	52
Table NA.H.4 — Minimum masonry compressive strengths with significant floor restraint .....	53
Table NA.H.5 — Absorbable spectral acceleration for shear wall cross-sectional areas of $p_{A,vorh} = 12$ % or (20 %) for the cross-sectional area of shear walls relative to the floor plan area as a percentage, with significant floor restraint .....	54
Table NA.H.6 — Minimum requirements for the cross-sectional area of shear walls relative to the floor plan area as a percentage, with little floor restraint for spectral accelerations of $\leq 1,25$ m/s <sup>2</sup> and 1,70 m/s <sup>2</sup> .....	55

Table NA.H.7 — Minimum requirements for the cross-sectional area of shear walls relative to the floor plan area as a percentage, with little floor restraint for spectral accelerations of 2,10 m/s <sup>2</sup> and 2,60 m/s <sup>2</sup> .....	56
Table NA.H.8 — Minimum requirements for the cross-sectional area of shear walls relative to the floor plan area as a percentage, with little floor restraint for spectral accelerations of 3,00 m/s <sup>2</sup> and 3,60 m/s <sup>2</sup> .....	57
Table NA.H.9 — Absorbable spectral acceleration for shear wall cross-sectional areas of $p_{A,vorh} = 12\%$ or (20 %) for the cross-sectional area of shear walls relative to the floor plan area as a percentage with little floor restraint .....	58
Table NA.H.10 — Minimum requirements for the cross-sectional area of shear walls made of aerated concrete relative to the floor plan area, with significant floor restraint for spectral accelerations of $\leq 1,25\text{ m/s}^2$ ; $1,70\text{ m/s}^2$ and $2,10\text{ m/s}^2$ .....	59
Table NA.H.11 — Minimum requirements for the cross-sectional area of shear walls made of aerated concrete masonry relative to the floor plan area, with significant floor restraint for spectral accelerations of $2,60\text{ m/s}^2$ ; $3,00\text{ m/s}^2$ and $3,60\text{ m/s}^2$ .....	60
Table NA.H.12 — Absorbable spectral acceleration for shear wall cross-sectional areas of $p_{A,vorh} = 12\%$ or (20 %) for the cross-sectional area of shear walls made of aerated concrete masonry relative to the floor plan area as a percentage, with significant floor restraint.....	61
Table NA.H.13 — Minimum requirements for the cross-sectional area of shear walls made of aerated concrete masonry relative to the floor plan area, with little floor restraint for spectral accelerations of $\leq 1,25\text{ m/s}^2$ ; $1,70\text{ m/s}^2$ and $2,10\text{ m/s}^2$ .....	62
Table NA.H.14 — Minimum requirements for the cross-sectional area of shear walls made of aerated concrete masonry relative to the floor plan area, with little floor restraint for spectral accelerations of $2,60\text{ m/s}^2$ and $3,00\text{ m/s}^2$ as well as absorbable spectral acceleration for shear wall cross-sectional areas of $p_{A,vorh} = 12\%$ or (20 %) .....	63