

# ISO 23327:2021-09 (E)

## Hygrothermal performance of building materials and products - Determination of moisture adsorption/desorption properties in response to periodic temperature variation

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Specimen .....</b>	<b>1</b>
<b>5</b>	<b>Test apparatus .....</b>	<b>2</b>
<b>5.1</b>	<b>General .....</b>	<b>2</b>
<b>5.2</b>	<b>Sealed box .....</b>	<b>2</b>
<b>5.3</b>	<b>Box or chamber with thermostat .....</b>	<b>4</b>
<b>5.4</b>	<b>Thermometer .....</b>	<b>4</b>
<b>5.5</b>	<b>Hygrometer .....</b>	<b>4</b>
<b>6</b>	<b>Curing and thermal insulation of specimen .....</b>	<b>4</b>
<b>6.1</b>	<b>Damp-proofing of specimen .....</b>	<b>4</b>
<b>6.2</b>	<b>Curing of specimen .....</b>	<b>5</b>
<b>6.3</b>	<b>Thermal insulation of specimen .....</b>	<b>5</b>
<b>7</b>	<b>Test method .....</b>	<b>6</b>
<b>7.1</b>	<b>Cleaning inside the sealed box .....</b>	<b>6</b>
<b>7.2</b>	<b>Initial relative humidity inside the sealed box .....</b>	<b>6</b>
<b>7.3</b>	<b>Installation of specimen .....</b>	<b>6</b>
<b>7.4</b>	<b>Placement of sealed box .....</b>	<b>6</b>
<b>7.5</b>	<b>Temperature conditions .....</b>	<b>7</b>
<b>7.6</b>	<b>Measurement .....</b>	<b>7</b>
<b>8</b>	<b>Water vapour leakage from sealed box .....</b>	<b>7</b>
<b>8.1</b>	<b>Calibration of sealed box for vapour leakage .....</b>	<b>7</b>
<b>8.2</b>	<b>Calculation of calibration value .....</b>	<b>8</b>
<b>8.3</b>	<b>Tolerance calibration value .....</b>	<b>8</b>
<b>9</b>	<b>Calculation of results .....</b>	<b>8</b>
<b>9.1</b>	<b>Temperature and humidity in sealed box .....</b>	<b>8</b>
<b>9.2</b>	<b>Moisture-adsorption/desorption amount .....</b>	<b>9</b>
<b>10</b>	<b>Test report .....</b>	<b>10</b>
<b>Annex A (informative) Temperature conditions of box or chamber with thermostat .....</b>		<b>11</b>