

DIN EN 1998-2/NA:2022-12 (E)

National Annex - Nationally determined parameters - Eurocode 8: Design of structures for earthquake resistance - Part 2: Bridges

Contents

	Page
Foreword	4
NA.1 Scope	5
NA.2 National provisions for the application of DIN EN 1998-2:2011-12	5
NA.2.1 General	5
NA.2.2 National provisions (Nationally determined parameters)	6
NDP re 1.1.1(8) Scope of DIN EN 1998-2	6
NCI re 1.2.4 Normative references	6
NCI re 2.1(2)P Design seismic action	7
NDP re 2.1(3)P Design seismic action	7
NDP re 2.1(4)P Design seismic action and 2.1(6)P Design seismic action	7
NDP re 2.2.2 (5) Ultimate limit states (ULS)	8
NDP re 2.3.5.3(1) Local ductility at the plastic hinges	8
NDP re 2.3.6.3(5) Control of displacements — Detailing	8
NDP re 2.3.7(1) Simplified criteria	8
NDP re 2.3.7(1) Simplified criteria	8
NDP re 3.2.2.3(1)P Near source effects	8
NDP re 3.3(1)P Spatial variability of the seismic action	8
NDP re 3.3(6)P Spatial variability of the seismic action	9
NDP re 3.3(6)P Spatial variability of the seismic action	9
NDP re 4.1.2(4)P Masses	9
NDP re 4.1.8(2)P Regular and irregular seismic behaviour of ductile bridges	9
NDP re 5.3(4) Capacity design	9
NDP re 5.4(1) Second order effects	9
NDP re 5.6.2(2)P Structures of limited ductile behaviour	9
NDP re 6.2.1.4(1)P Required confining reinforcement	9
NDP re 6.5.1(1)P Verification of ductility of critical sections	10
NDP re 6.6.2.3(3) Elastomeric bearings	10
NDP re 6.6.3.2(1)P Holding-down devices	10
NDP re 6.7.3(7) Abutments rigidly connected to the deck	10
NDP re 7.4.1(1)P Design spectra	10
NDP re 7.6.2(1)P Isolating system	10
NDP re 7.6.2(5) Isolating system	10
NDP re 7.7.1(2) Lateral restoring capability	10
NDP re J.1(2) Factors causing variation of design properties	10
NDP re J.2(1) Evaluation of the variation	10
Annex NA.A (informative) Simplified design rules for simple bridges	11
NA.A.1 General	11
NA.A.2 Determination of the horizontal seismic forces	12
NA.A.2.1 General	12
NA.A.2.2 Excitation in the longitudinal direction — use of movable bearings at the abutment	12
NA.A.2.3 Excitation in the longitudinal direction — use of fixed bearings at the abutment	13
NA.A.2.4 Excitation in the transverse direction	13
NA.A.3 Combination of the action effects due to the components of the seismic action	15
NA.A.4 Torsional effects (rotation about the vertical axis)	15
NA.A.5 Displacements, joints, minimum bearing lengths	15
NA.A.5.1 (Relative) displacements	15

NAA.5.2 Joints	16
NAA.5.3 Minimum overlap length.....	16
NAA.6 Stability analysis	17
NAA.7 Abutments and retaining walls.....	18
NAA.7.1 Abutments flexibly connected to the deck	18
NAA.7.2 Abutments rigidly connected to the deck	19
NAA.8 Bearings	19
NAA.8.1 Fixed bearings	19
NAA.8.2 Movable bearings	19
NAA.8.3 Elastomeric bearings.....	19
NAA.9 Avoidance of brittle fracture of specific non-ductile components.....	19
NAA.10 Special rules for concrete members	20
NAA.10.1 General	20
NAA.10.2 Confining reinforcement in piers.....	20

Figures

Figure NA.A.1 — Model of the excitation in the longitudinal direction where the deck is supported by fixed bearings at the abutment (elevation)	13
Figure NA.A.2 — Model of a beam bridge with horizontal forces — F_i due to excitation in the transverse direction (view from above)	14
Figure NA.A.3 — Minimum overlap length at the abutment if movable bearings are used.....	17

Tables

Table NA.1 — Importance classes and importance factors	8
Table NA.2 — Distance of abutments beyond which ground motions are to be considered as uncorrelated.....	9
Table NA.A.1 — Limits of the length of continuous bridge decks — L_{lim}	11