DIN EN 1999-1-5:2024-11 (E)

Eurocode 9 - Design of aluminium structures - Part 1-5: Shell structures

Contents

Page

European foreword 5

0 Introduction 6

1 Scope 8
1.2 Assumptions 9

2 Normative references 10

3 Terms, definitions and symbols 10
3.1 Terms and definitions 10
3.1.1 Structural forms and geometry 10
3.1.2 Special definitions for buckling calculations 11
3.2 Symbols 12
3.3 Sign conventions 16
3.4 Coordinate systems 16

4 Basis of design 18
4.1 General 18
4.2 Consequence class and execution class 18

5 Materials and geometry 19
5.1 Material properties 19
5.2 Design values of geometrical data 19
5.3 Geometrical tolerances and geometrical imperfections 19

6 Durability 19

7 Structural analysis 19
7.1 Geometry 19
7.2 Boundary conditions 20
7.3 Actions and environmental influences 21
7.4 Stress resultants and stresses 22
7.5 Types of analysis 22

8 Ultimate limit state 23
8.1 Resistance of cross section 23
8.1.1 Design values of stresses 23
8.1.2 Design values of resistance 24
8.1.3 Stress limitation 25
8.1.4 Design by numerical analysis 25
8.2 Buckling resistance 25
8.2.1 General 25
8.2.2 Buckling-relevant geometrical tolerances 26
8.2.3 Shell in compression and shear 27
8.2.4 Effect of welding 30
8.2.5 Design by numerical analysis 33

9 Serviceability limit states 33
9.1 General 33
9.2 Deflections 33

Annex A (normative) Formulae for shell buckling analysis 34

A.1 Use of this annex 34
A.2 Scope and field of application 34
A.3 Unstiffened cylindrical shells of constant wall thickness 34
A.3.1 Notations and boundary conditions 34
A.3.2 Meridional (axial) compression 35
A.3.3 Circumferential (hoop) compression 37
A.3.4 Shear 40
A.3.5 Meridional (axial) compression with coexistent internal pressure 41
A.3.6 Combinations of meridional (axial) compression, circumferential (hoop) compression and shear 42
A.4 Unstiffened cylindrical shells of stepwise wall thickness 44
A.4.1 General 44
A.4.2 Meridional (axial) compression 45
A.4.3 Circumferential (hoop) compression 45
A.4.4 Shear 49
A.5 Unstiffened lap jointed cylindrical shells 50
A.5.1 Geometry and stress resultants 50
A.5.2 Meridional (axial) compression 50
A.5.3 Circumferential (hoop) compression 50
A.5.4 Shear 51
A.6 Unstiffened conical shells 51
A.6.1 General 51
A.6.2 Design buckling stresses 52
A.6.3 Buckling strength verification 52
A.7 Stiffened cylindrical shells of constant wall thickness 53
A.7.1 General 53
A.7.2 Isotropic walls with meridional stiffeners 53
A.7.3 Isotropic walls with circumferential stiffeners 55
A.7.4 Circumferentially corrugated walls with meridional stiffeners 55
A.7.5 Axially corrugated walls with ring stiffeners 59
A.7.6 Stiffened wall treated as an orthotropic shell 60
A.7.7 Equivalent orthotropic properties of corrugated sheeting 63
A.8 Unstiffened spherical shells under uniform circumferential compression 64
A.8.1 Notations and boundary conditions 64
A.8.2 Critical buckling stresses 65
A.8.3 Circumferential buckling parameter 65

Annex B (informative) Formulae for buckling analysis of tori-conical and tori-spherical shells 67

B.1 Use of this Annex 67
B.2 Scope and field of application 67
B.3 Notations and boundary conditions 67
B.4 External pressure 68
B.4.1 Critical external pressure 68
B.4.2 Uniform squash limit external pressure 69
B.4.3 External pressure buckling parameter 71
B.5 Internal pressure 71
B.5.1 Critical internal pressure 71
B.5.2 Uniform squash limit internal pressure 72
B.5.3 Internal pressure buckling parameter 73

Bibliography 75