

DIN EN 12390-19:2023-07 (E)

Testing of hardened concrete - Part 19: Determination of electrical resistivity

| Contents | | Page |
|---|---|-------------|
| European foreword | | 3 |
| Introduction | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms, definitions and symbols | 5 |
| 3.1 | Terms and definitions | 5 |
| 3.2 | Symbols | 7 |
| 4 | Principle | 7 |
| 5 | Apparatus | 8 |
| 5.1 | Resistivity meter | 8 |
| 5.2 | Data logger | 9 |
| 5.3 | Electrodes | 9 |
| 5.4 | Sponges | 9 |
| 5.5 | Wetting liquid at the sponge/concrete interface | 10 |
| 6 | Preparation of test specimens | 10 |
| 6.1 | Minimum number of specimens/readings to obtain a test result for a concrete | 10 |
| 6.2 | Test specimen preparation | 11 |
| 7 | Test procedure volumetric method (reference method) | 11 |
| 7.1 | Determination of the volumetric resistance | 11 |
| 7.2 | Two-electrode arrangement | 13 |
| 8 | Test procedure surface method | 13 |
| 8.1 | Measurements | 13 |
| 8.2 | Calculation of resistivity | 15 |
| 8.2.1 | General | 15 |
| 8.2.2 | Volumetric method | 15 |
| 8.2.3 | Surface method | 15 |
| 9 | Test report | 16 |
| 10 | Precision | 17 |
| Annex A (informative) Determination of the precision of the equipment | | 18 |
| Bibliography | | 19 |