

DIN EN ISO 22097:2024-01 (E)

Thermal insulation for buildings - Reflective insulation products - Determination of thermal performance (ISO 22097:2023)

| Contents | | Page |
|--------------------------------|--|-------------|
| European foreword | | 4 |
| Foreword | | 5 |
| Introduction | | 6 |
| 1 | Scope | 7 |
| 2 | Normative references | 7 |
| 3 | Terms, definitions and symbols | 8 |
| | 3.1 Terms and definitions | 8 |
| | 3.2 Symbols and units | 8 |
| 4 | Description of product types | 9 |
| | 4.1 Product classification | 9 |
| | 4.2 Product Type 1 | 9 |
| | 4.3 Product Type 2 | 10 |
| | 4.4 Product Type 3 | 10 |
| | 4.5 Product Type 4 | 11 |
| 5 | Methods of assessment | 12 |
| | 5.1 General | 12 |
| | 5.2 Thickness measurement | 12 |
| | 5.3 Test specimens | 12 |
| | 5.3.1 Size and number of specimens | 12 |
| | 5.3.2 Conditioning and specimen preparation | 12 |
| | 5.4 Determination of thermal resistance — Outline | 13 |
| | 5.5 Determination of core thermal resistance of product Type 1 | 13 |
| | 5.5.1 Test thicknesses | 13 |
| | 5.5.2 Product thickness greater than 20 mm | 13 |
| | 5.5.3 Product thickness less than or equal to 20 mm | 14 |
| | 5.5.4 For all thicknesses and nominal thermal resistances | 14 |
| | 5.6 Determination of core thermal resistance of Product Type 2 | 14 |
| | 5.6.1 General | 14 |
| | 5.6.2 Product Type 2 with surface indentations less than 2 mm in depth | 14 |
| | 5.6.3 Product Type 2 with surface indentations greater than or equal to 2 mm, but less than 5 mm in depth | 14 |
| | 5.6.4 Product Type 2 with surface indentations 5 mm in depth or greater | 14 |
| | 5.6.5 For either all thicknesses or nominal thermal resistances, or both | 15 |
| | 5.7 Determination of core thermal resistance of product Type 3 (Method C) | 15 |
| | 5.7.1 Principle | 15 |
| | 5.7.2 Determination of the need for specimen conditioning | 15 |
| | 5.7.3 Air cavity and specimen installation | 15 |
| | 5.7.4 Hot box test conditions | 18 |
| | 5.7.5 Allowance for heat transfer around the specimen (edge surround) | 18 |
| | 5.7.6 Calculating the core thermal resistance of the product | 20 |
| | 5.8 Determination of the thermal performance of product Type 4 | 20 |
| | 5.9 Emissivity | 21 |
| | 5.9.1 General | 21 |
| | 5.9.2 Measurement of emissivity | 21 |

| | | |
|----------|---|-----------|
| 6 | Uncertainty | 22 |
| 6.1 | General..... | 22 |
| 6.2 | Thickness measurements..... | 22 |
| 6.3 | Use of thermocouples on thin samples in a guarded hot plate or in heat flow meter measurement..... | 22 |
| 6.4 | Use of dummy insulation specimens..... | 22 |
| 6.5 | Derivation of the core resistance of a Type 3 product from hot box measurements..... | 22 |
| 7 | Expression of results | 23 |
| 7.1 | Results derived from hot plate and emissivity measurements (products Type 1 and 2)..... | 23 |
| 7.2 | Results derived from hot box and emissivity measurements (product Types 1, 2 and 3)..... | 23 |
| 7.3 | Results derived from emissivity measurements only (product Type 4)..... | 24 |
| 8 | Report | 24 |
| | Annex A (normative) Decision making flow chart for identification of product types | 25 |
| | Annex B (normative) Selection of test methodology for product type 1 when using a hot plate method | 26 |
| | Annex C (normative) Selection of the measurement technique for Product Type 2 | 27 |
| | Annex D (normative) Measurement of emissivity using a thermal infra-red apparatus | 28 |
| | Annex E (normative) “Dummy specimen” technique for the heat flow meter apparatus | 34 |
| | Bibliography | 36 |