

# DIN EN 1993-3-1/NA:2024-09 (E)

## National Annex - Nationally determined parameters - Eurocode 3: Design of steel structures - Part 3-1: Towers, masts and chimneys - Towers and masts

---

| <b>Contents</b>                       | <b>Page</b> |
|---------------------------------------|-------------|
| Foreword .....                        | 5           |
| NA.1 Scope .....                      | 6           |
| NA.2.1 General .....                  | 6           |
| NA.2.2 National provisions .....      | 7           |
| NCI re 1.2 Normative references ..... | 7           |
| NDP re 2.1.1(3)P .....                | 8           |
| NDP re 2.3.1(1) .....                 | 8           |
| NDP re 2.3.2(1) .....                 | 8           |
| NDP re 2.3.6(2) .....                 | 8           |
| NDP re 2.3.7(1) .....                 | 9           |
| NDP re 2.3.7(4) .....                 | 9           |
| NDP re 2.5(1) .....                   | 9           |
| NDP re 2.6(1) .....                   | 9           |
| NDP re 4.1(1) .....                   | 9           |
| NDP re 4.2(1) .....                   | 9           |
| NDP re 5.1(6) .....                   | 9           |
| NDP re 5.2.4(1) .....                 | 9           |
| NDP re 6.1(1) .....                   | 9           |
| NDP re 6.3.1(1) .....                 | 10          |
| NDP re 6.4.1(1) .....                 | 10          |
| NDP re 6.4.2(2) .....                 | 10          |
| NDP re 6.5.1(1) .....                 | 10          |
| NDP re 7.1(1) .....                   | 10          |
| NCI re 9.1 .....                      | 10          |
| NDP re 9.5(1) .....                   | 10          |
| NDP re A.1(1) .....                   | 11          |

|   |           |
|---|-----------|
| NDP re A.2(1)P (2 places) .....                                       | 11        |
| NCI re Annex B .....  | 11        |
| NCI re Annex C .....  | 11        |
| NDP re D.1.1(2) .....   | 11        |
| NDP re D.1.2(2) .....   | 11        |
| NDP re D.3(6) (2 places) .....  | 11        |
| NDP re D.4.1(1) .....   | 12        |
| NDP re D.4.2(3) .....   | 12        |
| NDP re D.4.3(1) .....   | 12        |
| NDP re D.4.4(1) .....   | 12        |
| NCI re Annex F .....  | 12        |
| <b>Annex NA.B (normative) Assumptions for wind actions .....</b>      | <b>13</b> |
| <b>NA.B.1 NCI General .....</b>                                       | <b>13</b> |
| <b>NA.B.1.1 NCI Scope .....</b>                                       | <b>13</b> |
| <b>NA.B.1.2 NCI Symbols and indices .....</b>                         | <b>13</b> |
| <b>NA.B.2 NCI Wind force coefficient .....</b>                        | <b>14</b> |
| <b>NA.B.2.1 NCI General .....</b>                                     | <b>14</b> |
| <b>NA.B.2.2 NCI Reference area .....</b>                              | <b>15</b> |
| <b>NA.B.2.3 NCI Determination of the wind force coefficient .....</b> | <b>15</b> |
| <b>NA.B.3 NCI Gust response of lattice towers .....</b>               | <b>24</b> |
| <b>NA.B.3.1 NCI Criteria for static methods .....</b>                 | <b>24</b> |
| <b>NA.B.3.2 NCI Equivalent static method .....</b>                    | <b>25</b> |
| <b>NA.B.3.3 NCI Crosswind vortex vibrations .....</b>                 | <b>26</b> |
| <b>NA.B.4 NCI Response of guyed masts .....</b>                       | <b>27</b> |
| <b>NA.B.4.1 NCI General .....</b>                                     | <b>27</b> |
| <b>NA.B.4.2 NCI Criteria for static methods .....</b>                 | <b>27</b> |
| <b>NA.B.4.3 NCI Equivalent static methods .....</b>                   | <b>28</b> |
| <b>NA.B.4.4 NCI Spectral analysis method .....</b>                    | <b>32</b> |
| <b>NA.B.4.5 NCI Vortex-excited vibrations .....</b>                   | <b>32</b> |
| <b>NA.B.4.6 NCI Guy vibrations .....</b>                              | <b>33</b> |
| <b>NA.B.4.7 NCI Natural frequency of free-standing towers .....</b>   | <b>34</b> |

|  |           |
|--|-----------|
| <b>NA.B.4.8 NCI Natural frequency for cantilevered guyed masts .....</b>                         | <b>34</b> |
| <b>Annex NA.C (normative) Ice loading and combinations of ice with wind .....</b>                | <b>36</b> |
| <b>NA.C.1 NCI General .....</b>  | <b>36</b> |
| <b>NA.C.2 NCI Ice loading .....</b>  | <b>36</b> |
| <b>NA.C.3 NCI Ice weight .....</b>   | <b>37</b> |
| <b>NA.C.4 NCI Wind and ice .....</b>   | <b>37</b> |
| <b>Annex NA.F (normative) Execution and monitoring of conditions .....</b>                       | <b>38</b> |
| <b>NA.F.1 NCI Execution .....</b>  | <b>38</b> |
| <b>NA.F.2 NCI Monitoring of conditions .....</b>   | <b>39</b> |
| <b>NA.F.3 NCI Main inspection .....</b>  | <b>39</b> |
| <b>Annex NA.I (normative) Additional technical regulations .....</b>                             | <b>40</b> |
| <b>NA.I.1 NCI Persons falling in safety harnesses .....</b>                                      | <b>40</b> |
| <b>NA.I.2 NCI Information on the calculation of bracing .....</b>                                | <b>40</b> |
| <b>NA.I.3 NCI Bolted connections .....</b>   | <b>40</b> |
| <b>NA.I.4 NCI Minimum thickness .....</b>  | <b>40</b> |
| <b>NA.I.5 NCI Cross-section bracing .....</b>  | <b>40</b> |
| <b>NA.I.6 NCI Wire rope grips .....</b>  | <b>41</b> |
| <b>NA.I.7 NCI Bolts .....</b>  | <b>41</b> |
| <b>NA.I.8 NCI Insulators and protective fittings .....</b>                                       | <b>41</b> |
| <b>NA.I.8.1 NCI General .....</b>  | <b>41</b> |
| <b>NA.I.8.2 NCI Ceramic insulators .....</b>   | <b>41</b> |
| <b>NA.I.8.3 NCI Safety and routine testing of ceramic insulators subjected to pressure .....</b> | <b>42</b> |
| <b>NA.I.8.4 NCI Other insulators .....</b>   | <b>42</b> |
| <b>NA.I.9 NCI Foundations .....</b>  | <b>42</b> |
| <b>NA.I.9.1 NCI Concrete foundations .....</b>   | <b>42</b> |
| <b>NA.I.9.2 NCI Anchoring .....</b>  | <b>42</b> |
| <b>NA.I.9.3 NCI Auxiliary anchors .....</b>  | <b>43</b> |
| <b>NA.I.10 NCI Corrosion protection .....</b>  | <b>43</b> |
| <b>NA.I.10.1 NCI General .....</b>   | <b>43</b> |
| <b>NA.I.10.2 NCI Coatings .....</b>  | <b>43</b> |
| <b>NA.I.11 NCI Lightning protection and earthing systems .....</b>                               | <b>44</b> |

|   |    |
|---|----|
| NA.I.12 NCI Installation aids .....   | 45 |
| NA.I.13 NCI Equipment for accessing and inspecting the structure, fall protection .....   | 45 |
| NA.I.13.1 NCI General .....   | 45 |
| NA.I.13.2 NCI Ladders .....   | 45 |
| NA.I.13.3 NCI Safety equipment on working platforms and walkways .....  | 45 |
| NA.I.13.4 NCI Access to guys .....  | 46 |
| NA.I.13.5 NCI Openings in hollow masts .....  | 46 |
| Bibliography .....  | 47 |
| Figures Figure NA.B.1 -- Definition of the face .....   | 16 |
| Figure NA.B.2 -- Wind incidence factor K .....  | 19 |
| Figure NA.B.3 -- Force coefficients $c_{f,S,0}$ for lattice structures with square or triangular cross-section .....  | 21 |
| Figure NA.B.4 -- Load cases for lattice towers .....  | 25 |
| Figure NA.B.5 -- Application of patch loads .....   | 30 |
| Figure NA.B.6 -- Typical wind directions to be considered .....   | 31 |
| Figure NA.B.7 -- Example of the effective length $L_j$ for guyed masts .....  | 32 |
| Figure NA.B.8 -- Basic value $c_{lat,0}$ for the aerodynamic excitation force coefficient as a function of the strake length $l_w$ (applies for $Sc \geq 8$ ) ..... | 33 |
| Figure NA.B.9 -- Coefficients for determining the natural frequency according to Equation (NA.B.29) .....   | 35 |
| Figure NA.F.1 -- Erection tolerances .....  | 39 |
| Figure NA.I.1 -- Example of the earthing of a guyed mast .....  | 45 |
| Tables Table NA.1 -- Characteristic values for the Hertz pressure of steel bearings .....   | 10 |
| Table NA.A.2 -- Partial factors G and Q for actions .....   | 11 |
| Table NA.B.1 -- Typical force coefficients, $c_{f,A,0}$ and $c_{f,G,0}$ , for individual members .....  | 22 |
| Table NA.I.1 -- Ceramic insulators .....  | 42 |