

# DIN EN 1993-3-1/NA:2024-09 (E)

## National Annex - Nationally determined parameters - Eurocode 3: Design of steel structures - Part 3-1: Towers, masts and chimneys - Towers and masts

---

<b>Contents</b>	<b>Page</b>
Foreword .....	5
NA.1 Scope .....	6
NA.2.1 General .....	6
NA.2.2 National provisions .....	7
NCI re 1.2 Normative references .....	7
NDP re 2.1.1(3)P .....	8
NDP re 2.3.1(1) .....	8
NDP re 2.3.2(1) .....	8
NDP re 2.3.6(2) .....	8
NDP re 2.3.7(1) .....	9
NDP re 2.3.7(4) .....	9
NDP re 2.5(1) .....	9
NDP re 2.6(1) .....	9
NDP re 4.1(1) .....	9
NDP re 4.2(1) .....	9
NDP re 5.1(6) .....	9
NDP re 5.2.4(1) .....	9
NDP re 6.1(1) .....	9
NDP re 6.3.1(1) .....	10
NDP re 6.4.1(1) .....	10
NDP re 6.4.2(2) .....	10
NDP re 6.5.1(1) .....	10
NDP re 7.1(1) .....	10
NCI re 9.1 .....	10
NDP re 9.5(1) .....	10
NDP re A.1(1) .....	11

NDP re A.2(1)P (2 places) .....	11
NCI re Annex B .....	11
NCI re Annex C .....	11
NDP re D.1.1(2) .....	11
NDP re D.1.2(2) .....	11
NDP re D.3(6) (2 places) .....	11
NDP re D.4.1(1) .....	12
NDP re D.4.2(3) .....	12
NDP re D.4.3(1) .....	12
NDP re D.4.4(1) .....	12
NCI re Annex F .....	12
<b>Annex NA.B (normative) Assumptions for wind actions .....</b>	<b>13</b>
<b>NA.B.1 NCI General .....</b>	<b>13</b>
<b>NA.B.1.1 NCI Scope .....</b>	<b>13</b>
<b>NA.B.1.2 NCI Symbols and indices .....</b>	<b>13</b>
<b>NA.B.2 NCI Wind force coefficient .....</b>	<b>14</b>
<b>NA.B.2.1 NCI General .....</b>	<b>14</b>
<b>NA.B.2.2 NCI Reference area .....</b>	<b>15</b>
<b>NA.B.2.3 NCI Determination of the wind force coefficient .....</b>	<b>15</b>
<b>NA.B.3 NCI Gust response of lattice towers .....</b>	<b>24</b>
<b>NA.B.3.1 NCI Criteria for static methods .....</b>	<b>24</b>
<b>NA.B.3.2 NCI Equivalent static method .....</b>	<b>25</b>
<b>NA.B.3.3 NCI Crosswind vortex vibrations .....</b>	<b>26</b>
<b>NA.B.4 NCI Response of guyed masts .....</b>	<b>27</b>
<b>NA.B.4.1 NCI General .....</b>	<b>27</b>
<b>NA.B.4.2 NCI Criteria for static methods .....</b>	<b>27</b>
<b>NA.B.4.3 NCI Equivalent static methods .....</b>	<b>28</b>
<b>NA.B.4.4 NCI Spectral analysis method .....</b>	<b>32</b>
<b>NA.B.4.5 NCI Vortex-excited vibrations .....</b>	<b>32</b>
<b>NA.B.4.6 NCI Guy vibrations .....</b>	<b>33</b>
<b>NA.B.4.7 NCI Natural frequency of free-standing towers .....</b>	<b>34</b>

<b>NA.B.4.8 NCI Natural frequency for cantilevered guyed masts .....</b>	<b>34</b>
<b>Annex NA.C (normative) Ice loading and combinations of ice with wind .....</b>	<b>36</b>
<b>NA.C.1 NCI General .....</b>	<b>36</b>
<b>NA.C.2 NCI Ice loading .....</b>	<b>36</b>
<b>NA.C.3 NCI Ice weight .....</b>	<b>37</b>
<b>NA.C.4 NCI Wind and ice .....</b>	<b>37</b>
<b>Annex NA.F (normative) Execution and monitoring of conditions .....</b>	<b>38</b>
<b>NA.F.1 NCI Execution .....</b>	<b>38</b>
<b>NA.F.2 NCI Monitoring of conditions .....</b>	<b>39</b>
<b>NA.F.3 NCI Main inspection .....</b>	<b>39</b>
<b>Annex NA.I (normative) Additional technical regulations .....</b>	<b>40</b>
<b>NA.I.1 NCI Persons falling in safety harnesses .....</b>	<b>40</b>
<b>NA.I.2 NCI Information on the calculation of bracing .....</b>	<b>40</b>
<b>NA.I.3 NCI Bolted connections .....</b>	<b>40</b>
<b>NA.I.4 NCI Minimum thickness .....</b>	<b>40</b>
<b>NA.I.5 NCI Cross-section bracing .....</b>	<b>40</b>
<b>NA.I.6 NCI Wire rope grips .....</b>	<b>41</b>
<b>NA.I.7 NCI Bolts .....</b>	<b>41</b>
<b>NA.I.8 NCI Insulators and protective fittings .....</b>	<b>41</b>
<b>NA.I.8.1 NCI General .....</b>	<b>41</b>
<b>NA.I.8.2 NCI Ceramic insulators .....</b>	<b>41</b>
<b>NA.I.8.3 NCI Safety and routine testing of ceramic insulators subjected to pressure .....</b>	<b>42</b>
<b>NA.I.8.4 NCI Other insulators .....</b>	<b>42</b>
<b>NA.I.9 NCI Foundations .....</b>	<b>42</b>
<b>NA.I.9.1 NCI Concrete foundations .....</b>	<b>42</b>
<b>NA.I.9.2 NCI Anchoring .....</b>	<b>42</b>
<b>NA.I.9.3 NCI Auxiliary anchors .....</b>	<b>43</b>
<b>NA.I.10 NCI Corrosion protection .....</b>	<b>43</b>
<b>NA.I.10.1 NCI General .....</b>	<b>43</b>
<b>NA.I.10.2 NCI Coatings .....</b>	<b>43</b>
<b>NA.I.11 NCI Lightning protection and earthing systems .....</b>	<b>44</b>

NA.I.12 NCI Installation aids .....	45
NA.I.13 NCI Equipment for accessing and inspecting the structure, fall protection .....	45
NA.I.13.1 NCI General .....	45
NA.I.13.2 NCI Ladders .....	45
NA.I.13.3 NCI Safety equipment on working platforms and walkways .....	45
NA.I.13.4 NCI Access to guys .....	46
NA.I.13.5 NCI Openings in hollow masts .....	46
Bibliography .....	47
Figures Figure NA.B.1 -- Definition of the face .....	16
Figure NA.B.2 -- Wind incidence factor K .....	19
Figure NA.B.3 -- Force coefficients $c_{f,S,0}$ for lattice structures with square or triangular cross-section .....	21
Figure NA.B.4 -- Load cases for lattice towers .....	25
Figure NA.B.5 -- Application of patch loads .....	30
Figure NA.B.6 -- Typical wind directions to be considered .....	31
Figure NA.B.7 -- Example of the effective length $L_j$ for guyed masts .....	32
Figure NA.B.8 -- Basic value $clat,0$ for the aerodynamic excitation force coefficient as a function of the strake length $l_w$ (applies for $Sc \geq 8$ ) .....	33
Figure NA.B.9 -- Coefficients for determining the natural frequency according to Equation (NA.B.29) .....	35
Figure NA.F.1 -- Erection tolerances .....	39
Figure NA.I.1 -- Example of the earthing of a guyed mast .....	45
Tables Table NA.1 -- Characteristic values for the Hertz pressure of steel bearings .....	10
Table NA.A.2 -- Partial factors G and Q for actions .....	11
Table NA.B.1 -- Typical force coefficients, $c_{f,A,0}$ and $c_{f,G,0}$ , for individual members .....	22
Table NA.I.1 -- Ceramic insulators .....	42