DIN 18008-4:2024-12 (E)

Glass in building - Design and construction rules - Part 4: Additional requirements for barrier glazing

Contents

Page

Foreword 5

1 Scope 6

2 Normative references 8

3 Terms and definitions, symbols and units 8
3.1 Terms and definitions 8
3.2 Symbols and units 9
3.2.1 Latin capital letters 9
3.2.2 Latin small letters 9
3.2.3 Greek small letters 9

4 Construction products 10

5 Application conditions 10
5.1 Verification of edge protection 10
5.2 Effectiveness of edge protection strips 10
5.3 Category B glazing 11

6 Effects of actions and verification 11
6.1 General 11
6.2 Ultimate limit state for static actions 13
6.2.1 General 13
6.2.2 Persistent/transient design situation (GZT-P) 13
6.2.3 Accidental design situation (GZT-A) 14
6.3 Ultimate limit state for impacts 14
6.3.1 General 14
6.3.2 Verification of edge protection fulfilled 15
6.3.3 Verification of edge protection not fulfilled 15

Annex A (normative) Verification of the impact resistance of glazing through building component tests 16

A.1 Pendulum impact test 16
A.2 Penetration test 20
A.3 Test report 21

Annex B (normative) Constructions with experimentally verified impact resistance 22

B.1 Linearly supported glazing units of Categories A and C 22
B.2 Point-fixed glazing units of Categories A and C 24
B.3 Linearly supported glazing Category B 26

Annex C (normative) Verification of impact resistance of glass structures by calculation 28

C.1 Calculation principles 28
C.1.1 General 28
C.1.2 Design conditions 28
C.1.3 Exposure to stress 28
C.1.4 Resistance 28

C.1.5 Verification of impact resistance of insulating glass units 29
C.1.6 Verification of impact resistance of laminated safety glass 29
C.1.7 Overlaying of impact loads with other actions 29
C.2 Simplified verification procedure 29
C.2.1 Calculation principles 29
C.2.2 Exposure to stress 30
C.2.3 Verification 30
C.3 Verification by means of fully dynamic transient simulation of impact event 32
C.3.1 General 32
C.3.2 Verification 32
C.3.3 Proof 36

Annex D (normative) Verification of impact resistance of supporting structures 37

D.1 Linear support structures 37
D.1.1 Screwed fastenings 37
D.1.2 Other types of fastening 37
D.2 Point-fixed support structures 37

Annex E (normative) Verification of edge protection by component testing 38

E.1 General 38
E.2 Test procedure 38
E.3 Test report 38

Annex F (normative) Effective edge protection, verified by testing 42

Bibliography 43

Figures

Figure 1 -- Examples for Categories A, B and C 7

Figure 2 -- Verification for Category A 11

Figure 3 -- Verification for Category B 12

Figure 4 -- Verification for Category C 13

Figure A.1 -- Diagram of pendulum impact apparatus 16

Figure A.2 -- Detail of impact body 17

Figure A.3 -- Examples of impact surfaces 19

Figure A.4 -- Testing apparatus for penetration test 21

Figure B.1 -- Permissible deviations from the rectangular shape illustrated by the example of a glazing unit supported on two sides 22

Figure B.2 -- Dimensions and configuration of point-fixed glazing 25

Figure B.3 -- Permissible deviations from rectangular shape 27

Figure B.4 -- Schematic diagram of Category B glass parapet 27

Figure C.1 -- Impact transmission coefficient for glass sheets linearly supported on two sides depending on the equivalent stiffness kGlasplatte 31

Figure C.2 -- Acceleration sequence of the pendulum body in the case of impact against a rigid wall 32

Figure C.3 -- Acceleration sequence of the pendulum body in the case of impact in the centre of a glass sheet supported on four sides with the dimensions 876 mm × 1 938 mm, glass thickness t = 8 mm 33

Figure C.4 -- Main stress sequence in the centre of a glass sheet on the side less likely to receive impact in the case of mid-sheet impact against a glass sheet supported on four sides with the dimensions 876 mm × 1 938 mm, glass thickness t = 8 mm 34

Figure C.5 -- Acceleration sequence of the pendulum body in the case of mid-sheet impact against a glass sheet supported on two sides with the dimensions 700 mm × 1 000 mm, glass thickness t = 8 mm, span 1 000 mm 35

Figure C.6 -- Main stress sequence in the centre of a glass sheet in the case of mid-sheet impact against a glass sheet supported on two sides with the dimensions 700 mm × 1 000 mm, glass thickness t = 8 mm, span 1 000 mm 36

Figure E.1 -- Location of impact points for a hard impact, illustrated by the example of a horizontal glass edge 39

Figure E.2 -- Location of impact points for a hard impact, illustrated by the example of a vertical glass edge 40

Figure E.3 -- Definition of surface of the edge and corner of the edge 41

Figure F.1 -- Edge protection 42

Tables

Table A.1 -- Pendulum drop heights h for the categories for various scenarios 18

Table B.1 -- Linearly supported glazing units with verified impact resistance 23

Table B.2 -- Point-fixed glazing units with verified impact resistance 25

Table C.1 -- Modification factors kmod for impact stress with light impact 29