

DIN 18008-5:2024-12 (E)

Glass in Building - Design and construction rules - Part 5: Additional requirements for walk-on glazing

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Terms and definitions, symbols and units	4
3.1	Terms and definitions	4
3.2	Symbols and units	5
4	Construction products	5
5	Application conditions	5
6	Effects of actions and verification	5
6.1	Limit states for static loads	5
6.2	Limit states for impact actions and residual load-bearing capacity	6
Annex A (normative)	Verification of impact resistance and residual load-bearing capacity by building component tests	7
A.1	General	7
A.2	Test procedure	7
A.2.1	Verification of impact resistance	7
A.2.2	Verification of residual load-bearing capacity	8
A.2.3	Test report	8
Annex B (normative)	Glass constructions with empirically verified impact resistance and residual load-bearing capacity	10
B.1	General	10
B.2	Glazing units linearly supported on all sides	10
Bibliography		12
 Figures		
Figure A.1	— Schematic diagram of the impact body	7
Figure B.1	— Diagram of bearing depth	11
 Tables		
Table B.1	— Glazing units linearly supported on all sides and intended as walk-on glazing, with verified impact resistance and residual load-bearing capacity	10