

DIN EN 1366-9:2025-04 (E)

Fire resistance tests for service installations - Part 9: Single compartment smoke extraction ducts

Contents		Page
European foreword		5
Introduction		7
1	Scope	8
2	Normative references	8
3	Terms and definitions	9
4	Test equipment	10
4.1	General	10
4.2	Furnace	10
4.3	Perforated plate	10
4.4	Air velocity measuring station	11
4.5	Ambient temperature leakage measuring device	11
4.6	Pressure sensors for differential pressure control	11
4.7	Welded connecting tube	11
4.8	Extract fan connecting duct	11
4.9	Extraction fan	12
4.10	Thermocouples	12
4.11	Oxygen measuring equipment	12
4.12	Oxygen measurement probes	12
4.13	Restraint equipment	12
4.14	Deflection measurements	12
5	Test conditions	12
5.1	Differential pressure conditions	12
5.2	Heating and pressure conditions	12
6	Test specimen	13
6.1	Size	13
6.1.1	Length	13
6.1.2	Cross-section	13
6.2	Number	13
6.3	Design	13
7	Installation of test specimen	14
7.1	General	14
7.2	Supporting construction	14
7.3	Duct arrangement	14
7.4	Restraint of ducts	14
7.4.1	Inside the furnace	14
7.4.2	Outside the furnace	14
7.5	Perforated plate	15
8	Conditioning	15
8.1	General	15
8.2	Water based sealing materials	15
9	Application of instrumentation	15

9.1	Thermocouples	15
9.1.1	Furnace thermocouples (plate thermometers)	15
9.1.2	Gas temperature within flow nozzles	15
9.2	Pressure	15
9.2.1	Furnace pressure	15
9.2.2	Differential under-pressure in duct	15
9.3	Oxygen measurements	16
9.4	Deflection measurement for determination of reduction of internal cross-sectional area ..	16
10	Test procedure	17
10.1	Pre-test adjustment	17
10.1.1	Oxygen-measuring instrument	17
10.1.2	Perforated plate	17
10.2	Leakage measurement at ambient temperature	17
10.3	Pre-fire test procedures	18
10.4	Fire test	18
10.5	Termination of test	19
11	Performance criteria	20
11.1	General requirements	20
11.2	Criteria at ambient temperature	20
11.2.1	Ambient leakage	20
11.2.2	Maintenance of cross-section under ambient conditions outside the furnace	20
11.3	Criteria under fire conditions	20
11.3.1	General	20
11.3.2	Integrity	20
11.3.3	Smoke leakage	21
12	Test report	21
13	Direct field of application of test results	21
13.1	General	21
13.2	Duct sizes	22
13.3	Suspension device	22
13.4	Pressure difference	22
13.5	Vertical part of duct	22
13.6	Steel ducts	22
Annex A (informative) Measurement of volume/mass flow		36
A.1	Hints on measuring volume flow or mass flow with differential pressure devices	36
A.2	Density	36
A.3	Absolute pressure (barometric pressure)	36
A.4	Viscosity	37
A.5	Characteristic data of the inlet nozzles according to Figure 10	37
Annex B (informative) Measurement of oxygen content		40
B.1	Details on measuring oxygen content with parametric cell analysers	40
B.2	Choice of O ₂ measuring devices	40
B.3	Effect of O ₂ measuring device errors	41
B.4	Zero and end point drift	41
B.5	Details on the creation of an oxygen content from 12,5 to 13,5 vol % within the furnace	
	43 Annex C (informative) The usage of correction factors for the consideration of	
	different parameters	44
C.1	Details for the development of the correction factors and their error limits	44
C.2	The complete formula for the leakage mass flow and the parameters	44
C.3	Application of correction factors in the simple mass flow formulae and achievable	
	accuracy	47
Bibliography		49