

# DIN EN 13084-1:2025-04 (E)

## Free-standing chimneys - Part 1: General requirements

---

<b>Contents</b>		<b>Page</b>
European foreword .....		4
<b>1</b>	<b>Scope .....</b>	<b>6</b>
<b>2</b>	<b>Normative references .....</b>	<b>6</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>6</b>
<b>3.1</b>	<b>General terms .....</b>	<b>7</b>
<b>3.2</b>	<b>Terms for chimney parts .....</b>	<b>8</b>
<b>3.3</b>	<b>Terms for operation .....</b>	<b>9</b>
<b>4</b>	<b>General requirements .....</b>	<b>10</b>
<b>4.1</b>	<b>Materials .....</b>	<b>10</b>
<b>4.2</b>	<b>Flue gas considerations .....</b>	<b>10</b>
<b>4.2.1</b>	<b>General .....</b>	<b>10</b>
<b>4.2.2</b>	<b>Design parameters .....</b>	<b>11</b>
<b>4.2.3</b>	<b>Heat flow calculations .....</b>	<b>11</b>
<b>4.2.4</b>	<b>Flow calculations .....</b>	<b>14</b>
<b>4.2.5</b>	<b>Chemical attack .....</b>	<b>14</b>
<b>4.3</b>	<b>Environmental aspects .....</b>	<b>17</b>
<b>4.3.1</b>	<b>Pollutants dispersion .....</b>	<b>17</b>
<b>4.3.2</b>	<b>Noise .....</b>	<b>17</b>
<b>4.3.3</b>	<b>Temperature .....</b>	<b>17</b>
<b>4.3.4</b>	<b>Fire .....</b>	<b>17</b>
<b>4.3.5</b>	<b>Gas tightness .....</b>	<b>17</b>
<b>4.4</b>	<b>Connecting flue pipe .....</b>	<b>18</b>
<b>4.5</b>	<b>Insulation .....</b>	<b>18</b>
<b>4.6</b>	<b>Ventilation .....</b>	<b>19</b>
<b>4.7</b>	<b>Protective coatings .....</b>	<b>19</b>
<b>4.8</b>	<b>Foundation .....</b>	<b>20</b>
<b>4.9</b>	<b>Accessories .....</b>	<b>20</b>
<b>4.9.1</b>	<b>Access .....</b>	<b>20</b>
<b>4.9.2</b>	<b>Lightning protection .....</b>	<b>21</b>
<b>4.9.3</b>	<b>Aircraft warning system .....</b>	<b>21</b>
<b>4.9.4</b>	<b>Additional accessories .....</b>	<b>21</b>
<b>5</b>	<b>Performance requirements: Structural design .....</b>	<b>22</b>
<b>5.1</b>	<b>Basic design principles .....</b>	<b>22</b>
<b>5.2</b>	<b>Actions .....</b>	<b>23</b>
<b>5.2.1</b>	<b>General .....</b>	<b>23</b>
<b>5.2.2</b>	<b>Permanent actions .....</b>	<b>23</b>
<b>5.2.3</b>	<b>Variable actions .....</b>	<b>23</b>
<b>5.2.4</b>	<b>Accidental actions .....</b>	<b>25</b>
<b>5.3</b>	<b>Imperfections .....</b>	<b>25</b>
<b>5.4</b>	<b>Foundation .....</b>	<b>26</b>
<b>5.5</b>	<b>Liner .....</b>	<b>26</b>
<b>6</b>	<b>Site activities .....</b>	<b>26</b>
<b>7</b>	<b>Lifetime management, monitoring, inspection, maintenance, cleaning, repair and remedial work including the reporting; operations and actions required .....</b>	<b>26</b>

<b>8</b>	<b>Instrumentation .....</b>	<b>26</b>
	<b>Annex A (normative) Gas flow calculation .....</b>	<b>28</b>
<b>A.1</b>	<b>Principal features of the method of calculation .....</b>	<b>28</b>
<b>A.2</b>	<b>Parameters related to construction type .....</b>	<b>28</b>
<b>A.2.1</b>	<b>Roughness .....</b>	<b>28</b>
<b>A.2.2</b>	<b>Thermal resistance .....</b>	<b>28</b>
<b>A.3</b>	<b>Basic values for the calculation .....</b>	<b>29</b>
<b>A.3.1</b>	<b>Air temperature .....</b>	<b>29</b>
<b>A.3.2</b>	<b>Outside air pressure .....</b>	<b>29</b>
<b>A.3.3</b>	<b>Flue gas .....</b>	<b>29</b>
<b>A.3.4</b>	<b>Gas constant .....</b>	<b>30</b>
<b>A.3.5</b>	<b>Density of outside air .....</b>	<b>31</b>
<b>A.3.6</b>	<b>Specific heat capacity .....</b>	<b>31</b>
<b>A.3.7</b>	<b>Correction factor for temperature .....</b>	<b>31</b>
<b>A.3.8</b>	<b>Flow safety coefficient .....</b>	<b>32</b>
<b>A.4</b>	<b>Determination of temperatures .....</b>	<b>32</b>
<b>A.4.1</b>	<b>Flue gas temperatures .....</b>	<b>32</b>
<b>A.4.2</b>	<b>Coefficient of cooling .....</b>	<b>32</b>
<b>A.4.3</b>	<b>Heat transmission coefficient .....</b>	<b>33</b>
<b>A.4.4</b>	<b>Internal heat transfer coefficient .....</b>	<b>33</b>
<b>A.5</b>	<b>Density of flue gas .....</b>	<b>35</b>
<b>A.6</b>	<b>Flue gas velocity .....</b>	<b>35</b>
<b>A.7</b>	<b>Pressure at entry of flue gas into chimney .....</b>	<b>35</b>
<b>A.7.1</b>	<b>Calculation of pressure .....</b>	<b>35</b>
<b>A.7.2</b>	<b>Theoretical draught available due to chimney effect .....</b>	<b>36</b>
<b>A.7.3</b>	<b>Pressure resistance of the flue gas carrying tube .....</b>	<b>36</b>
<b>A.7.4</b>	<b>Flue friction coefficient .....</b>	<b>36</b>
<b>A.7.5</b>	<b>Individual resistance coefficient .....</b>	<b>37</b>
<b>A.7.6</b>	<b>Change in pressure due to change of velocity .....</b>	<b>37</b>
<b>A.7.7</b>	<b>Pressure caused by sudden interruption of the flue gas stream (Implosion) .....</b>	<b>37</b>
<b>A.8</b>	<b>Minimum velocity .....</b>	<b>38</b>
	<b>Annex B (informative) Calculation method for combined flue gases with different temperatures .....</b>	<b>43</b>
	<b>Bibliography .....</b>	<b>46</b>